



**SAFETY DATA SHEET**  
**P101 2 PACK POLYURETHANE FOR FLOORS - HARDENER**

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME P101 2 PACK POLYURETHANE FOR FLOORS - HARDENER  
 PRODUCT NO. 150/P101/POLY - HARDENER  
 APPLICATION HARDENER FOR TWO COMPONENT SURFACE COATING FOR FLOORS  
 SUPPLIER COO-VAR  
 Lockwood Street  
 Hull  
 HU2 0HN  
 01482 328053  
 01482 219266  
 info@coo-var.co.uk  
 CONTACT PERSON as above

### 2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
2-METHOXY-1-METHYLETHYL ACETATE	203-603-9	108-65-6	10-30%	R10 Xi;R36
ALIPHATIC POLYISOCYANATE		28182-81-2	60-100%	R43.
ETHYLBENZENE	202-849-4	100-41-4	1-5%	F;R11 Xn;R20
HEXAMETHYLENE-DI-ISOCYANATE	212-485-8	822-06-0	< 1	T;R23 R42/43 Xi;R36/37/38
XYLENE	215-535-7	1330-20-7	10-30%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

### 3 HAZARDS IDENTIFICATION

Flammable. Harmful by inhalation. May cause sensitisation by inhalation and skin contact.

CLASSIFICATION Xn;R20. R42/43. R10.

### 4 FIRST-AID MEASURES

#### GENERAL INFORMATION

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious.

#### INHALATION

Remove victim immediately from source of exposure. In case of persistent throat irritation or coughing: Seek medical attention and take along these instructions. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues. Place unconscious person on the side in the recovery position and ensure breathing

#### INGESTION

DO NOT induce vomiting. Get medical attention immediately. Provide fresh air, warmth and rest, preferably in comfortable upright sitting position.

#### SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.

#### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Continue to rinse for at least 15 minutes and get medical attention.

### 5 FIRE-FIGHTING MEASURES

**P101 2 PACK POLYURETHANE FOR FLOORS - HARDENER****EXTINGUISHING MEDIA**

Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

**SPECIAL FIRE FIGHTING PROCEDURES**

Be aware of danger for fire to re-start. Cool containers exposed to flames with water until well after the fire is out. Do not allow runoff to sewer, waterway or ground.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

FLAMMABLE. Solvent vapours may form explosive mixtures with air.

**SPECIFIC HAZARDS**

In case of fire, toxic and corrosive gases may be formed.

**PROTECTIVE MEASURES IN FIRE**

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Do not smoke, use naked flames or other sources of ignition. Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area.

**ENVIRONMENTAL PRECAUTIONS**

Do not allow to enter drains, sewers or watercourses. Remove mechanically; cover the remainder with wet absorbent material (eg. sawdust, chemical binder based on calcium silicate hydrate, sand). After approximately one hour transfer to waste container and do not seal (evolution of CO<sub>2</sub>). Further disposal: Storage on approved landfill or special refuse dump, or by incineration.

**SPILL CLEAN UP METHODS**

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Ventilate well.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Persons with impaired lung functions should not handle this preparation. Observe workplace exposure limits and minimise the risk of inhalation of vapours and mist. Spraying is permitted only in closed systems, spray cabinets or spray boxes with adequate ventilation. Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Do not eat, drink or smoke when using the product. The Manual Handling Operations Regulations may apply to the handling of containers of this product. For products sold by weight refer to the guide net weight indicated on the container. Allowance will have to be made for the immediate packaging to give an approximate gross weight.

**USAGE DESCRIPTION**

Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container

**STORAGE PRECAUTIONS**

Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep upright. Store separated from: Oxidising material. Alkalies. Acids.

**STORAGE CLASS**

Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 50 litres of liquids with a flashpoint below 32°C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	LT - ppm	LT - mg/m <sup>3</sup>	ST - ppm	ST - mg/m <sup>3</sup>
XYLENE	WEL	50 ppm(Sk)	220 mg/m <sup>3</sup> (Sk)	100 ppm(Sk)	441 mg/m <sup>3</sup> (Sk)
ETHYLBENZENE	WEL	100 ppm(Sk)	441 mg/m <sup>3</sup> (Sk)	125 ppm(Sk)	552 mg/m <sup>3</sup> (Sk)
HEXAMETHYLENE-DI-ISOCYANATE	WEL		0.02 mg/m <sup>3</sup> (Sen)		0.07 mg/m <sup>3</sup> (Sen)
2-METHOXY-1-METHYLETHYL ACETATE	WEL	50 ppm(Sk)	274 mg/m <sup>3</sup> (Sk)	100 ppm(Sk)	548 mg/m <sup>3</sup> (Sk)
ALIPHATIC POLYISOCYANATE	WEL	0.02 ppm Sen		0.07 ppm Sen	

**INGREDIENT COMMENTS**

WEL = Workplace Exposure Limits

**P101 2 PACK POLYURETHANE FOR FLOORS - HARDENER**

## PROTECTIVE EQUIPMENT



## ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of spray. Must not be handled in confined space without sufficient ventilation. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded. Explosion-proof general and local exhaust ventilation.

## RESPIRATORY EQUIPMENT

In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P2). At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used. Only PROFESSIONALS are permitted to apply this product by spray. Air-fed respiratory protective equipment with combined helmet and visor should be worn when this product is sprayed. This should be in addition to other measures to reduce exposure (e.g. in booth design and operation and process modifications).

## HAND PROTECTION

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

## EYE PROTECTION

Wear goggles/face shield. Wear splash-proof eye goggles to prevent any possibility of eye contact.

## OTHER PROTECTION

Wear appropriate clothing to prevent reasonably probable skin contact.

## HYGIENE MEASURES

No specific hygiene procedures noted, but good personal hygiene practices are always advisable, especially when working with chemicals.

## PERSONAL PROTECTION

Unprotected persons should be kept away from treated areas.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Liquid		
COLOUR	Yellowish		
ODOUR	Characteristic of solvents		
SOLUBILITY	Insoluble in water Hardens in contact with water.		
BOILING POINT (°C)	145 760 mm Hg	RELATIVE DENSITY	1.06 - 1.08 @ 20 C
VAPOUR PRESSURE	Xylene ca. 7-9 @ 20 C, Hexamethylene-1,6-diisocyanat e 0.014 @ 25 C, Resin <0.001@ 20 C (Vapour pressure balance/OECD No. 104 mbar	VISCOSITY	ca. 225 mPa.s @ 23 C DIN EN ISO 3219/A.3 - ca. 59 s 4mm flow cup to DIN 53211
FLASH POINT (°C)	38 approx. CC (Closed cup).	AUTO IGNITION TEMPERATURE (°C)	460 C DIN 51794
FLAMMABILITY LIMIT - LOWER(%)	Xylene = 1% - 1-methoxypropylacetate-2= 1.5%	FLAMMABILITY LIMIT - UPPER(%)	Xylene=8%, 1-methoxypropylacetate-2=10.8 %

**10 STABILITY AND REACTIVITY**

## STABILITY

Stable under normal temperature conditions and recommended use.

## CONDITIONS TO AVOID

Exothermic reaction with amines and alcohols; reacts slowly with water forming CO<sub>2</sub>, in closed containers risk of bursting owing to increase of pressure.

## MATERIALS TO AVOID

Strong alkalis. Strong acids. Strong oxidising substances.

## HAZARDOUS DECOMPOSITION PRODUCTS

None under normal conditions.

**P101 2 PACK POLYURETHANE FOR FLOORS - HARDENER****11 TOXICOLOGICAL INFORMATION**

TOXIC DOSE 1 - LD 50 >5000 mg/kg (oral rat)

**TOXICOLOGICAL INFORMATION**

Skin and mucous membrane compatibility, rabbit: Skin - 4 hours exposure - very slight irritant. Eyes - very slight irritant. No pulmonary sensitisation observed in animal tests. No pulmonary sensitisation potential was observed in the guinea pig model after either intradermal or inhalative induction with polyisocyanate based on hexamethylene diisocyanate. Skin sensitisation according to Buehler (epicutaneous test). In the guinea pig the product did not show a sensitising effect. Skin sensitivity according to Magnusson/Kligmann (maximising test). In the guinea pig the product has a sensitising effect. Salmonella/microsome test (Ames test). No indication of mutagenic effects. No indication of mutagenic effects. Subacute inhalation toxicity, rat. Test concentration - 4, 3; 14, 7 and 98, 8 mg aerosol/m<sup>3</sup> - exposure time - 3 weeks (6 hours a day, 5 days a week) OECD No. 413; 1985 ----- 4, 3mg/m<sup>3</sup> was tolerated without damage (NOEL), 14, 7 mg/m<sup>3</sup> caused increased lung weight, 89, 8 mg/m<sup>3</sup> inflammatory changes in the respiratory tract. Evidence of damage to organs other than the organs of respiration was not found. Subchronic inhalation toxicity, rat: Test concentration - 0, 5; 3, 3; and 26, 4 mg aerosol/m<sup>3</sup>. exposure time - 13 weeks (6 hours a day, 5 days a week) OECD No. 413; 1987. ----- 3, 3 mg/m<sup>3</sup> was tolerated without damage (NOEL), 26, 4 mg/m<sup>3</sup> caused increased lung weight, indications of inflammatory changes in the respiratory tract. All the changes were unspecific and are attributed to the primary irritation potential of the product. Evidence of damage to organs other than the organs of respiration was not found. Aromatic hydrocarbons, such as xylene, irritate the skin and mucous membranes and are narcotic if inhaled in high concentrations.

**GENERAL INFORMATION**

Preparation contains small volumes of isocyanate which may cause allergic reaction and irritation of respiratory system.

**INHALATION**

Vapour from this chemical can be hazardous when inhaled. Vapour may irritate respiratory system or lungs.

**INGESTION**

Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

**SKIN CONTACT**

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

**EYE CONTACT**

May cause temporary eye irritation.

**HEALTH WARNINGS**

This product has low toxicity. Only large volumes may have adverse impact on human health.

**MEDICAL CONSIDERATIONS**

Skin disorders and allergies. Avoid vomiting and normal rinse of stomach because of risk of aspiration.

**SPECIFIC EFFECTS**

Over exposure, especially during spraying without the necessary precautions, entails risk of concentration- dependant irritating effects on eyes, nose, throat and respiratory tract. Delayed appearance of the complaints and development of hypersensitivity (difficulty breathing, coughing, asthma) are possible. Hypersensitive persons may suffer from these effects even at low isocyanate concentrations below UK Workplace Exposure Limits (WEL). Prolonged contact with skin may have tanning and irritating effects.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

The product contains a substance which may cause long term adverse effects in the aquatic environment. Dangerous for the environment: Toxic to soil organisms. Do not allow to escape into waters, wastewater or soil. The resin reacts with water at the interface forming CO<sub>2</sub> and a solid insoluble product with high melting point (polyurea). This reaction is accelerated by surfactants (eg. detergents) or by water soluble solvents.

LC 50, 96 Hrs, FISH mg/l LC(0) =8.8. LC(100)=25.0

EC 50, 48 Hrs, DAPHNIA, mg/l 100-1000

**MOBILITY**

Mobile.

**BIOACCUMULATION**

The product contains potentially bioaccumulating substances.

**DEGRADABILITY**

The product is not expected to be biodegradable.

**13 DISPOSAL CONSIDERATIONS**

## P101 2 PACK POLYURETHANE FOR FLOORS - HARDENER

**GENERAL INFORMATION**

Do not allow to enter drains, sewers or watercourses. When handling waste, consideration should be made to the safety precautions applying to handling of the product. May be incinerated in a suitable facility provided local regulations are observed.

**DISPOSAL METHODS**

Empty containers may be disposed of after neutralising any product remaining on the walls of the container with a mixture of isopropanol, ammonia and water. Afterwards remove warning labels.

**WASTE CLASS**

Neutralised empty packages, are categorised as non-hazardous waste, with code 15 01 02(plastic packaging) or 15 01 04 (metal packaging) If mixed with other wastes, the above waste code may not be applicable.

### 14 TRANSPORT INFORMATION



UK ROAD CLASS	3.3		
PROPER SHIPPING NAME	Resin solution		
ROAD TRANSPORT NOTES	Avoid releasing to the environment.		
RAIL TRANSPORT NOTES	Avoid releasing to the environment.		
SEA TRANSPORT NOTES	Do not release into the environment.		
UN NO. ROAD	1866	UK ROAD PACK GR.	III
ADR CLASS NO.	1263	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	HAZARD NO. (ADR)	30 Flammable liquid (flash-point between 23°C and 61°C, inclusive) or flammable liquid or solid in the molten state with a flash-point above 61°C, heated to a temperature equal to or above its flash-point, or self heating liquid.
	31C	CEVIC TEC(R) NO.	30GF1-III, 30GF1-sp
UN NO. SEA	1866	IMDG CLASS	3.3
IMDG PACK GR.	III	EMS	3-05
MARINE POLLUTANT		UN NO. AIR	1866



AIR CLASS	3.3	AIR PACK GR.	III
-----------	-----	--------------	-----

### 15 REGULATORY INFORMATION

**LABELLING**



Harmful

**CONTAINS**  
ALIPHATIC POLYISOCYANATE  
HEXAMETHYLENE-DI-ISOCYANATE

**RISK PHRASES**

R10	Flammable.
R20	Harmful by inhalation.

**P101 2 PACK POLYURETHANE FOR FLOORS - HARDENER**

R42/43 May cause sensitisation by inhalation and skin contact.

## SAFETY PHRASES

S2 Keep out of the reach of children  
 S23 Do not breathe vapour/spray.  
 S24 Avoid contact with skin.  
 S28 After contact with skin, wash immediately with plenty of water.  
 S29 Do not empty into drains.  
 S37 Wear suitable gloves.  
 S38 In case of insufficient ventilation, wear suitable respiratory equipment.  
 S45 In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).  
 S60 This material and its container must be disposed of as hazardous waste.  
 P4 Contains isocyanates. See information supplied by the manufacturer.

## UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations. The Control of Substances Hazardous to Health Regulations 1988. Health and Safety at Work Act 1974.

## ENVIRONMENTAL LISTING

Control of Pollution Act 1974. Rivers (Prevention of Pollution) Act 1961.

## EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EEC.

## STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

## APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

## GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

## NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits 2005 (EH40) Health and Safety at Work Act (As Amended) 1974 Control of Substances Hazardous to Health Regulations 2002 (as amended) The Carriage of Dangerous Goods and use of transportable pressure equipment regulations 2004. Dangerous Substances and Explosive Atmospheres Regulations 2002 [SI 2002: 2776] The Manual Handling Operations Regulations 1992 [SI 1992:2793]

**16 OTHER INFORMATION**

## REVISION COMMENTS

Major revision (CHIP3) Revisions to sections: (1), (2), (3), (8), (14), (15), and (16) Revision for WEL(Workplace Exposure Limit) section 8. Addition of references to Manual Handling Regulations and Dangerous Substances and Explosive Atmospheres Regulations (DSEAR) in Section 7; Classification of Wastes in Section 13; associated Regulatory References in Section 15.

## ISSUED BY

Technical Dept. (P.E.)

REVISION DATE 11/04/2006

REV. NO./REPL. SDS GENERATED 1

SDS NO. 10750

## SAFETY DATA SHEET STATUS

Approved.

DATE Date printed \_\_\_\_\_

SIGNATURE Initials \_\_\_\_\_

**P101 2 PACK POLYURETHANE FOR FLOORS - HARDENER**

## RISK PHRASES IN FULL

R10	Flammable.
R11	Highly flammable.
R20	Harmful by inhalation.
R20/21	Harmful by inhalation and in contact with skin.
R23	Toxic by inhalation.
R36	Irritating to eyes.
R36/37/38	Irritating to eyes, respiratory system and skin.
R38	Irritating to skin.
R42/43	May cause sensitisation by inhalation and skin contact.
R43	May cause sensitisation by skin contact.

## DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.