



SAFETY DATA SHEET LINEMARKER PAINT AEROSOL

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	LINEMARKER PAINT AEROSOL
PRODUCT NO.	141/Q108/ ALL COLOURS
APPLICATION	Paint
SUPPLIER	COO-VAR Lockwood Street Hull HU2 0HN +44 (0) 1482 328053(T) +44 (0) 1482 219266(F) info@coo-var.co.uk
CONTACT PERSON	Technical Department - 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri as above

2 HAZARDS IDENTIFICATION

Extremely flammable Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Irritating to eyes. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION (1999/45) Xi;R36. F+;R12. R52/53, R66, R67.

ENVIRONMENT

The product contains a substance which is very toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

PHYSICAL AND CHEMICAL HAZARDS

The product is extremely flammable and may ignite in the air at normal temperature and pressure. Explosive vapour/air mixtures may be spontaneously formed. Aerosol containers can explode when heated, due to excessive pressure build-up. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Do not pierce or burn even after use.

HUMAN HEALTH

Gas or vapour is harmful on prolonged exposure or in high concentration. In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling contents of this container is dangerous and can be fatal.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
PROPANE	200-827-9	74-98-6	30-60%	F+;R12
BUTANE	203-448-7	106-97-8	30-60%	F+;R12
ACETONE	200-662-2	67-64-1	10-30%	F;R11 Xi;R36 R66 R67
SOLVENT NAPHTHA, LIGHT AROMATIC	265-199-0	64742-95-6	5-10%	Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.
2-BUTOXYETHANOL	203-905-0	111-76-2	1-5%	Xn;R20/21/22 Xi;R36/38
1-METHOXY-2-PROPANOL	203-539-1	107-98-2	1-5%	R10 R67

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if he is unconscious.

LINEMARKER PAINT AEROSOL

INHALATION

In case of inhalation of spray mist: Move person into fresh air and keep at rest. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

Immediately rinse mouth and provide fresh air. DO NOT induce vomiting. Get medical attention immediately.

SKIN CONTACT

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. DO NOT use solvents or thinners

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Extinguish with foam, carbon dioxide, dry powder or water fog.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray should be used to cool containers. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.

UNUSUAL FIRE & EXPLOSION HAZARDS

Extremely flammable. Forms explosive mixtures with air. May travel considerable distance to source of ignition and flash back. Aerosol cans may explode in a fire.

SPECIFIC HAZARDS

Aerosol containers can explode when heated, due to excessive pressure build-up.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Avoid inhalation of vapours and aerosol spray.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses. Contain spillages with sand, earth or any suitable adsorbent material.

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb spillage with non-combustible, absorbent material. Let evaporate. Keep out of confined spaces because of explosion risk.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray near naked flame or any incandescent material.

STORAGE PRECAUTIONS

Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Do not pierce or burn even after use.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

LINEMARKER PAINT AEROSOL

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
1-METHOXY-2-PROPANOL	WEL	100 ppm(Sk)	375 mg/m3(Sk)	150 ppm(Sk)	560 mg/m3(Sk)	
2-BUTOXYETHANOL	WEL	25 ppm(Sk)		50 ppm(Sk)		
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3	
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
PROPANE		Asphyxiating	Asphyxiating	Asphyxiating	Asphyxiating	
SOLVENT NAPHTHA, LIGHT AROMATIC	SUP		600 mg/m3			

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits SUP = Supplier's recommendation.

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of spray.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used.

HAND PROTECTION

Due to the packaging form, aerosol, risk of skin contact is small. For prolonged or repeated skin contact use suitable protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Use eye protection. Wear approved chemical safety goggles where eye exposure is reasonably probable.

OTHER PROTECTION

Wear appropriate clothing to prevent reasonably probable skin contact.

HYGIENE MEASURES

Wash hands after handling. Wash promptly if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin.

PERSONAL PROTECTION

When using do not smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol		
COLOUR	Various colours		
ODOUR	of solvents		
PHYSICAL DATA COMMENTS	Information given concerns the major ingredient. 23 Flammable gas		
FLASH POINT (°C)	< -40C	AUTO IGNITION TEMPERATURE (°C)	410 - 580 C
FLAMMABILITY LIMIT - LOWER(%)	1.8	FLAMMABILITY LIMIT - UPPER(%)	9.5

10 STABILITY AND REACTIVITY

STABILITY

Avoid: Heat, sparks, flames.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

LINEMARKER PAINT AEROSOL

HAZARDOUS DECOMPOSITION PRODUCTS

In case of fire, toxic gases (CO, CO₂, NO_x) may be formed.

11 TOXICOLOGICAL INFORMATION

GENERAL INFORMATION

Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

INHALATION

In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. Unconsciousness and possible death. Gas or vapour in high concentrations may irritate respiratory system.

SKIN CONTACT

Repeated exposure may cause skin dryness or cracking.

EYE CONTACT

Irritating to eyes. Spray and vapour in the eyes may cause irritation and smarting.

HEALTH WARNINGS

Arrhythmia, (deviation from normal heart beat). Irritating to eyes. Gas or vapour may irritate respiratory system.

ROUTE OF ENTRY

Inhalation.

TARGET ORGANS

Central nervous system Respiratory system, lungs

MEDICAL SYMPTOMS

Arrhythmia, (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness. Skin irritation. Irritation of eyes and mucous membranes.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product has not been tested but contains ingredients which are toxic or very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Do not puncture or incinerate even when empty.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). **DO NOT BURN OR INCINERATE CONTAINERS EVEN WHEN EMPTY - CONTAINERS MAY BURST OR EXPLODE VIOLENTLY IF EXPOSED TO EXTREME HEAT.**

14 TRANSPORT INFORMATION

GENERAL

This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.



UK ROAD CLASS	2, 5F	UK ROAD PACK GR.	n/a
PROPER SHIPPING NAME	AEROSOL DISPENSERS NOS	ADR CLASS	Class 2.1: Flammable gases.
UN NO. ROAD	1950	TUNNEL RESTRICTION CODE	(E)
ADR CLASS NO.	2, 5F		
ADR PACK GROUP	N/A		

LINEMARKER PAINT AEROSOL

ADR LABEL NO.	2.1	CEFIC TEC(R) NO.	20G5F
UN NO. SEA	1950	IMDG CLASS	2
IMDG PAGE NO.	2102	IMDG PACK GR.	n/a
EMS	F-D, S-U	MFAG	see guide
UN NO. AIR	1950	AIR CLASS	2
AIR SUB CLASS	2.1		

15 REGULATORY INFORMATION

LABELLING



Irritant



Extremely Flammable

RISK PHRASES

R12	Extremely flammable.
R36	Irritating to eyes.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S2	Keep out of the reach of children.
S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.

UK REGULATORY REFERENCES

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Chemicals (Hazard Information & Packaging) Regulations.

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC.

STATUTORY INSTRUMENTS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health. The Aerosol Dispensers Regulations 1977 & 1999.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. British Aerosol Manufacturers Code of Practice 7th. Edition 1999.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. The Aerosol Dispensers (EEC Requirements) (Amendment) Regulations 1996 (S.I 1996 No. 2421).

16 OTHER INFORMATION

REVISION COMMENTS

Issued in new format for Reach compliance Issued in compliance with 30th & 31st ATP to Council Directive 67/548, as detailed in Commission Directive 2004/73/EC (1st ATP of EC Regulation 1272/2008)

ISSUED BY

Technical Dept. (P.E.)

LINEMARKER PAINT AEROSOL

REVISION DATE 03/11/2010

REV. NO./REPL. SDS GENERATED 3

SDS NO. 10773

SAFETY DATA SHEET STATUS

Approved.

DATE Date printed _____

SIGNATURE Initials _____

RISK PHRASES IN FULL

- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
- R36 Irritating to eyes.
- R36/38 Irritating to eyes and skin.
- R37 Irritating to respiratory system.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.