



## SAFETY DATA SHEET

## PROFLOOR BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED &amp; YELLOW

## 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME PROFLOOR BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW  
 PRODUCT NO. 135/W222/65, 2, 1, 15, 766 & 776  
 APPLICATION BASE FOR TWO COMPONENT FLOOR COATING  
 SUPPLIER COO-VAR  
 Lockwood Street  
 Hull  
 HU2 0HN  
 +44 (0) 1482 328053(T)  
 +44 (0) 1482 219266(F)  
 info@coo-var.co.uk  
 CONTACT PERSON as above

## 2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
C8 - C10 Aliphatic Glycidyl Ether		68081-84-5	5-10%	Xi;R36/38. N;R51/53. R43.
Phenol Formaldehyde Polymer Glycidyl Ether		28064-14-4	10-30%	Xi;R36/38. N;R51/53. R43.
REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER AVERAGE MW<=700)	500-033-5	25068-38-6	30-60%	R43 Xi;R36/38 N;R51/53

The Full Text for all R-Phrases are Displayed in Section 16

## 3 HAZARDS IDENTIFICATION

May cause sensitisation by skin contact. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R36/38. R43. N;R51/53.

## PHYSICAL AND CHEMICAL HAZARDS

When handled correctly, undamaged units represent no danger.

## HUMAN HEALTH

The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals in contact with skin.

## 4 FIRST-AID MEASURES

## GENERAL INFORMATION

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious.

## INHALATION

Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues. Place unconscious person on the side in the recovery position and ensure breathing

## INGESTION

Immediately give a couple of glasses of water or milk, provided the victim is fully conscious. Do not induce vomiting. Get medical attention if any discomfort continues.

## SKIN CONTACT

Remove affected person from source of contamination. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water. Get medical attention if irritation persists after washing.

## EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention immediately. Continue to rinse.

# PROFLOOR BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW

## 5 FIRE-FIGHTING MEASURES

### EXTINGUISHING MEDIA

Non flammable at room temperature, but will burn. Use fire-extinguishing media appropriate for surrounding materials. Fire can be extinguished using: Water spray, fog or mist. Foam, carbon dioxide or dry powder.

### SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Containers close to fire should be removed or cooled with water.

### SPECIFIC HAZARDS

By heating and fire, harmful vapours/gases may be formed.

### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

### ENVIRONMENTAL PRECAUTIONS

Avoid discharge into drains, water courses or onto the ground. Contain spillages with sand, earth or any suitable adsorbent material. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

### SPILL CLEAN UP METHODS

Should be prevented from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Avoid inhalation of vapours. Avoid spilling, skin and eye contact. Do not eat, drink or smoke when using the product. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product. For products sold by weight refer to the guide net weight indicated on the container. Allowance will have to be made for the immediate packaging to give an approximate gross weight.

### USAGE DESCRIPTION

Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container

### STORAGE PRECAUTIONS

Store in tightly closed original container in a cool, dry well-ventilated place. Store in closed original container at temperatures between 5°C and 25°C. Protect from freezing and direct sunlight. Keep upright.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

### PROTECTIVE EQUIPMENT



### PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level.

### ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

**PROFLOOR BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW****HAND PROTECTION**

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

**EYE PROTECTION**

Wear approved chemical safety goggles where eye exposure is reasonably probable.

**OTHER PROTECTION**

Wear appropriate clothing to prevent reasonably probable skin contact.

**HYGIENE MEASURES**

No specific hygiene procedures noted, but good personal hygiene practices are always advisable, especially when working with chemicals.

**PERSONAL PROTECTION**

Unprotected persons should be kept away from treated areas.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Viscous Coloured liquid		
COLOUR	Red		
ODOUR	Sweetish		
SOLUBILITY	Immiscible with water		
BOILING POINT (°C)	>150 760 mm Hg	RELATIVE DENSITY	1.12 @ 25C
VAPOUR PRESSURE	<0.1 mbar @ 20 C	VOLATILE BY VOL. (%)	0 %
VISCOSITY	0.90 Pas @ 25 C	AUTO IGNITION TEMPERATURE (°C)	>200
VOLATILE ORGANIC COMPOUND (VOC)	0 g/litre		

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions and recommended use.

**CONDITIONS TO AVOID**

Not known.

**HAZARDOUS POLYMERISATION**

Will not occur

**MATERIALS TO AVOID**

Strong acids. Bases, alkalies (inorganic). Amines. Mercaptans (thiols).

**HAZARDOUS DECOMPOSITION PRODUCTS**

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

**11 TOXICOLOGICAL INFORMATION****TOXICOLOGICAL INFORMATION**

No data recorded.

**GENERAL INFORMATION**

No specific health warnings noted.

**INHALATION**

May cause irritation to the respiratory system.

**INGESTION**

Harmful if swallowed. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

**SKIN CONTACT**

Irritating to skin. May cause sensitisation by skin contact.

**EYE CONTACT**

Irritating to eyes.

## PROFLOOR BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW

### HEALTH WARNINGS

May cause sensitisation by skin contact. Delayed appearance of the complaints and development of hypersensitivity (difficulty breathing, coughing, asthma) are possible.

### ROUTE OF ENTRY

Inhalation. Skin absorption. Ingestion. Skin and/or eye contact.

### MEDICAL CONSIDERATIONS

Skin disorders and allergies.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

There are no data on the ecotoxicity of this product.

### MOBILITY

The product is non-volatile.

### BIOACCUMULATION

No data available on bioaccumulation.

### DEGRADABILITY

No data available.

### ACUTE FISH TOXICITY

Toxicity to bacteria, algae and higher marine organisms not tested. COD: Not determined

## 13 DISPOSAL CONSIDERATIONS

### GENERAL INFORMATION

Do not allow to enter drains, sewers or watercourses. Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority. When handling waste, consideration should be made to the safety precautions applying to handling of the product. DO NOT reuse containers containing residual product without commercial cleaning

### WASTE CLASS

Neutralised empty packages, are categorised as non-hazardous waste, with code 15 01 02(plastic packaging) or 15 01 04 (metal packaging) Ideally this component should be mixed with the appropriate hardener and allowed to react fully to produce a solid waste.

## 14 TRANSPORT INFORMATION

UK ROAD CLASS	9		
PROPER SHIPPING NAME	PAINT PRODUCT		
ROAD TRANSPORT NOTES	Avoid releasing to the environment. Environmentally hazardous substance		
RAIL TRANSPORT NOTES	Avoid releasing to the environment.		
SEA TRANSPORT NOTES	Do not release into the environment.		
UN NO. ROAD	3082	UK ROAD PACK GR.	III
ADR CLASS NO.	3082	ADR CLASS	Class 9: Other dangerous substances.
ADR PACK GROUP	III	RID CLASS NO.	9
RID PACK GROUP	III	UN NO. SEA	3082
IMDG CLASS	9	IMDG PACK GR.	III
UN NO. AIR	3082	AIR CLASS	9
AIR PACK GR.	III		

## 15 REGULATORY INFORMATION

### LABELLING



Irritant



Dangerous for the environment

**PROFLOOR BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW**

CONTAINS C8 - C10 Aliphatic Glycidyl Ether  
 Phenol Formaldehyde Polymer Glycidyl Ether  
 REACTION PRODUCT : BISPHENOL A-(EPICHLOROHYDRIN):EPOXY RESIN (NUMBER  
 AVERAGE MW<=700)

## RISK PHRASES

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 R43 May cause sensitisation by skin contact.  
 R36/38 Irritating to eyes and skin.

## SAFETY PHRASES

S2 Keep out of the reach of children  
 S24/25 Avoid contact with skin and eyes.  
 S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
 S29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
 S37 Wear suitable gloves.  
 S46 If swallowed, seek medical advice immediately and show this container or label.  
 S61 Avoid release to the environment. Refer to special instructions/safety data sheets.  
 S64 If swallowed, rinse mouth with water (only if the person is conscious).  
 P5 Contains epoxy constituents. See information supplied by the manufacturer.

## UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations. The Control of Substances Hazardous to Health Regulations 1988. Health and Safety at Work Act 1974.

## ENVIRONMENTAL LISTING

Control of Pollution Act 1974. Rivers (Prevention of Pollution) Act 1961.

## EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EEC.

## STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

## APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

## GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

## NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits 2005 (EH40) Health and Safety at Work Act (As Amended) 1974 Control of Substances Hazardous to Health Regulations 2002 (as amended) The Carriage of Dangerous Goods and use of transportable pressure equipment regulations 2004. The Manual Handling Operations Regulations 1992 [SI 1992:2793]

**16 OTHER INFORMATION**

## REVISION COMMENTS

Major revision (CHIP3) Revisions to sections: (1), (2), (3), (8), (14), (15), and (16) Revision for WEL(Workplace Exposure Limit) section 8. Addition of references to Manual Handling Regulations in Section 7; Classification of Waste in Section 13; associated Regulatory References in Section 15.

## ISSUED BY

Technical Dept. (P.E.)

REVISION DATE 31/05/2006

REV. NO./REPL. SDS GENERATED 1

SDS NO. 10801

## SAFETY DATA SHEET STATUS

Approved.

DATE Date printed \_\_\_\_\_

SIGNATURE Initials \_\_\_\_\_

**PROFLOOR BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW**

## RISK PHRASES IN FULL

R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**DISCLAIMER**

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.