



SAFETY DATA SHEET

2 PACK ZINC PHOSPHATE PRIMER - BASE - ALL COLOURS

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	2 PACK ZINC PHOSPHATE PRIMER - BASE - ALL COLOURS
PRODUCT NO.	514/Q113/224 - BASE
APPLICATION	BASE FOR TWO COMPONENT PRIMER
SUPPLIER	TEAL & MACKRILL LIMITED LOCKWOOD STREET HULL HU2 0HN +44(0)1482 320194(T) +44(0)1482 219266(F) info@teamac.co.uk
CONTACT PERSON	Technical Department - 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri as above

2 HAZARDS IDENTIFICATION

Highly flammable. Harmful by inhalation and in contact with skin. Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xn;R20/21. Xi;R36/38. R43. F;R11. N;R51/53.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
XYLENE	215-535-7	1330-20-7	10-30%	R10 Xn;R20/21 Xi;R38
BUTANONE	201-159-0	78-93-3	10-30%	F;R11 Xi;R36 R66 R67
Bisphenol A Epoxy Resin		25036-25-3	10-30%	Xi;R36/38. R43.
Zinc phosphate	231-944-3	7779-90-0	10-30%	N;R50/53.
TOLUENE	203-625-9	108-88-3	1-5%	F;R11 Repr.Cat.3;R63 Xn;R48/20,R65 Xi;R38 R67
ISO-BUTANOL	201-148-0	78-83-1	1-5%	R10 Xi;R37/38,R41 R67

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious.

INHALATION

Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues.

Place unconscious person on the side in the recovery position and ensure breathing

INGESTION

DO NOT induce vomiting. Get medical attention immediately. Provide fresh air, warmth and rest, preferably in comfortable upright sitting position.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Continue to rinse for at least 15 minutes and get medical attention.

2 PACK ZINC PHOSPHATE PRIMER - BASE - ALL COLOURS**5 FIRE-FIGHTING MEASURES****EXTINGUISHING MEDIA**

Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

SPECIAL FIRE FIGHTING PROCEDURES

Be aware of danger for fire to re-start. Cool containers exposed to flames with water until well after the fire is out. Do not allow runoff to sewer, waterway or ground.

UNUSUAL FIRE & EXPLOSION HAZARDS

FLAMMABLE. Solvent vapours may form explosive mixtures with air.

SPECIFIC HAZARDS

By heating and fire, harmful vapours/gases may be formed.

PROTECTIVE MEASURES IN FIRE

Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

6 ACCIDENTAL RELEASE MEASURES**PERSONAL PRECAUTIONS**

Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Do not smoke, use naked flames or other sources of ignition. Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground. Contain spillages with sand, earth or any suitable adsorbent material.

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Should be prevented from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. There is a danger that cloths and rags used to clean up a spill, or even any absorbant material may spontaneously combust. Any cloths should be washed in warm soapy water and disposed of without crumpling. Absorbants should be sprayed with water prior to disposal.

7 HANDLING AND STORAGE**USAGE PRECAUTIONS**

Observe workplace exposure limits and minimise the risk of inhalation of vapours and mist. Keep away from heat, sparks and open flame.

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Do not eat, drink or smoke when using the product. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

USAGE DESCRIPTION

Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container

STORAGE PRECAUTIONS

Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep upright. Store separated from: Oxidising material. Alkalies. Acids.

STORAGE CLASS

Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 50 litres of liquids with a flashpoint below 32C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

2 PACK ZINC PHOSPHATE PRIMER - BASE - ALL COLOURS

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
BUTANONE	WEL	200 ppm(Sk)	600 mg/m3(Sk)	300 ppm(Sk)	899 mg/m3(Sk)	
ISO-BUTANOL	WEL	50 ppm	154 mg/m3	75 ppm	231 mg/m3	
TOLUENE	WEL	50 ppm(Sk)	191 mg/m3(Sk)	100 ppm(Sk)	384 mg/m3(Sk)	
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT**ENGINEERING MEASURES**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent reasonably probable skin contact.

HYGIENE MEASURES

No specific hygiene procedures noted, but good personal hygiene practices are always advisable, especially when working with chemicals.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Grey or Red		
ODOUR	Characteristic		
SOLUBILITY	Immiscible with water		
BOILING POINT (°C)	79 @ 760 mm Hg	RELATIVE DENSITY	~1.5 - 1.7 depending on colour @ 20C
VAPOUR DENSITY (air=1)	heavier than air	VAPOUR PRESSURE	12.2 mm Hg @ 20C
VOLATILE BY VOL. (%)	approx. 55% when mixed with activator	VISCOSITY	2.5 - 2.5 Ps @ 25C
FLASH POINT (°C)	4 °C CC (Closed cup).	FLAMMABILITY LIMIT - LOWER(%)	1.8
VOLATILE ORGANIC COMPOUND (VOC)	413 (when mixed) g/litre		

10 STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with acids and oxidising substances.

2 PACK ZINC PHOSPHATE PRIMER - BASE - ALL COLOURS**MATERIALS TO AVOID**

Strong alkalis. Strong acids. Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

11 TOXICOLOGICAL INFORMATION**TOXICOLOGICAL INFORMATION**

Based on the properties of the epoxy constituents and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and irritant. It contains low molecular epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may lead to irritation and sensitisation, possibly with cross-sensitisation to other epoxies.

GENERAL INFORMATION

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

INHALATION

Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication. In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects. May cause irritation to the respiratory system. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

INGESTION

Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

SKIN CONTACT

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation. May cause sensitisation by skin contact. Risk of sensitisation or allergic reactions among sensitive individuals.

EYE CONTACT

Irritation of eyes and mucous membranes.

HEALTH WARNINGS

Irritating to skin. Irritant of eyes and mucous membranes. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

MEDICAL CONSIDERATIONS

Skin disorders and allergies. Avoid vomiting and normal rinse of stomach because of risk of aspiration.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

There are no data on the ecotoxicity of this product. The product has not been tested but contains ingredients which are toxic or very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment.

BIOACCUMULATION

The product contains potentially bioaccumulating substances.

DEGRADABILITY

The product is not expected to be biodegradable.

13 DISPOSAL CONSIDERATIONS**GENERAL INFORMATION**

Do not allow to enter drains, sewers or watercourses.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

WASTE CLASS

When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

14 TRANSPORT INFORMATION

2 PACK ZINC PHOSPHATE PRIMER - BASE - ALL COLOURS

GENERAL

This product is packed in accordance with the Limited Quantity Provisions of CDGCP2, ADR and IMDG.



UK ROAD CLASS	3		
PROPER SHIPPING NAME	PAINT		
RAIL TRANSPORT NOTES	Avoid releasing to the environment.		
UN NO. ROAD	1263	UK ROAD PACK GR.	II
ADR CLASS NO.	1263	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	II	TUNNEL RESTRICTION CODE	(D/E)
UN NO. SEA	1263	IMDG CLASS	3
IMDG PACK GR.	II	EMS	3-05
UN NO. AIR	1263	AIR CLASS	3
AIR PACK GR.	II		

15 REGULATORY INFORMATION

LABELLING



Harmful



Highly Flammable



Dangerous for the environment

CONTAINS

XYLENE
Bisphenol A Epoxy Resin

RISK PHRASES

R11	Highly flammable.
R20/21	Harmful by inhalation and in contact with skin.
R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37	Wear suitable protective clothing and gloves.
S51	Use only in well-ventilated areas.
S60	This material and its container must be disposed of as hazardous waste.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
P5	Contains epoxy constituents. See information supplied by the manufacturer.
S23	Do not breathe vapour/spray.
S24/25	Avoid contact with skin and eyes.
S33	Take precautionary measures against static discharges.
S29/35	Do not empty into drains; dispose of this material and its container in a safe way.

2 PACK ZINC PHOSPHATE PRIMER - BASE - ALL COLOURS

UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations. The Control of Substances Hazardous to Health Regulations 1988. Health and Safety at Work Act 1974.

ENVIRONMENTAL LISTING

Control of Pollution Act 1974. Rivers (Prevention of Pollution) Act 1961.

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits 2005 (EH40) Health and Safety at Work Act (As Amended) 1974 Control of Substances Hazardous to Health Regulations 2002 (as amended) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007) Dangerous Substances and Explosive Atmospheres Regulations 2002 [SI 2002: 2776] The Manual Handling Operations Regulations 1992 [SI 1992:2793]

16 OTHER INFORMATION

REVISION COMMENTS

Issued in new format for Reach compliance Corrections to Section 14, Transport Information Issued in compliance with 30th & 31st ATP to Council Directive 67/548, as detailed in Commission Directive 2004/73/EC (1st ATP of EC Regulation 1272/2008)

ISSUED BY

Technical Dept. (P.E.)

REVISION DATE 19/02/2010

REV. NO./REPL. SDS GENERATED 2

SDS NO. 10844

SAFETY DATA SHEET STATUS

Approved.

DATE Date Printed_____

SIGNATURE Initials_____

RISK PHRASES IN FULL

R10	Flammable.
R11	Highly flammable.
R20/21	Harmful by inhalation and in contact with skin.
R36	Irritating to eyes.
R36/38	Irritating to eyes and skin.
R37/38	Irritating to respiratory system and skin.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R63	Possible risk of harm to the unborn child.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.