

# TECHNICAL HEALTH AND DATA SHEET

PRODUCT:- ACRYLIC FOUNDATION BASE

REFERENCE:- W/463/1

COLOUR:- WHITE

FINISH:- SEMI-MATT

TYPE:- ACRYLIC COPOLYMER, WATER  
THINNABLE

TYPICAL SG:- 1.35 AT 20°C

TYPICAL VISCOSITY:- 3.0 POISE AT 25°C

TYPICAL TOTAL SOLIDS:- 52.6% BY WEIGHT

FLASH POINT:- NON-FLAMMABLE

RECOMMENDED THINNERS:- WATER

APPLICATION:- BRUSH, ROLLER OR SPRAY.  
DO NOT APPLY WHEN THE  
TEMPERATURE IS BELOW 5°C

\*COVERAGE GUIDE:- 7-10 SQ. METRES/LITRE

\*DRYING TIME:- SURFACE DRY - 30 MINS  
THROUGH DRY - 2 HOURS  
(COLD DAMP CONDITIONS WILL PROLONG THESE TIMES)

USES:- AS A DENSE MATT WHITE FOR  
LUMINOUS PAINT

STORAGE:- PROTECT FROM FROST AND  
ABNORMAL HEAT

HEALTH & SAFETY:- SEE SHEET HSD 'B'

\*BY BRUSH TO A DRIED FILM THICKNESS OF 25 MICRONS AT 20°C.

**COO-VAR**

PAINTS, PRIMERS & SPECIALISED COATINGS

Ellenshaw Works, Lockwood Street, HULL. HU2 0HN  
Telephone : 01482-328053 Fax: 01482-219266