## TECHNICAL INFORMATION

PRODUCT	SUITABLE SURFACES	TIN OR PACK SIZE	COLOURS	COVERAGE	DRY TIME	FINISH
P101 Anti-graffiti Coating	Wood, Brick, Masonry, Plaster	5kg (split between two packs).	Clear (Colours available to special order)	35-40 sqm per 5 kg	Touch dry: 4-6 hours Full cure: 5-7 days	Gloss
WB101 Anti-graffiti Coating	Wood, Brick, Masonry, Plaster	5kg (split between two packs).	Clear	5-8 sqm per kg	Touch dry: 1-2 hours Full cure: 5-7 days	Off gloss
Anti-graffiti Kit	Wood, Brick, Masonry, Plaster	2.5kg (split between two packs)	Clear	25-40 sqm per 5 kg	Touch dry: 1-2 hours Full cure: 5-7 days	Off gloss
GP101 Graffiti Protection System	Brick, Concrete/Render, Sandstone	2.5 litre, 5 litre.	Clear	8-10 sqm per litre	Touch dry: 1-2 hours Hard dry: 2 hours	Gloss Matt
GP101 Sealer Coat	Porous Surfaces	2.5 litre.	Clear	10-15 sqm per litre	Touch dry: 40 mins Hard dry: 2 hours	Off gloss
Vandalene Anti-climb	Wood, Metal, Masonry, Roof Felt	0.8kg, 2kg, 4kg.	Tile Red, Green, Black, Grey. Special colours to order.	2 sqm per kg to film thickness of 0.5mm	Non-drying	Semi-Matt
Graffiti Remover Liquid Aerosol	Graffiti covered surfaces, P101, WB101	400ml Aerosol (packed in 6's).	N/A	N/A	N/A	N/A
Graffiti Remover Wipes	Graffiti covered surfaces, P101, WB101	Pack of 2 tubs (each tub contains approx 100 wipes).	N/A	N/A	N/A	N/A
Glocote Fluorescent	Wood, Metal, Masonry	500ml, 1 litre, 2.5 litre, 5 litre.	Orange, Pink, Red Green, Yellow	13 sqm per litre	Touch dry: 3 hours Hard dry: 12 hours	Matt
Glocote Foundation	Wood, Metal, Masonry	500ml, 1 litre, 2.5 litre, 5 litre.	White	13 sqm per litre	Touch dry: 2 hours Hard dry: 12 hours	Matt
Glocote Protective	Wood, Metal, Masonry	500ml, 1 litre, 2.5 litre, 5 litre.	Clear	14 sqm per litre	Touch dry: 6 hours Hard dry: 24 hours	Gloss
Luminous Paint	Wood, Metal, Masonry	500ml 2.5 litre.	Translucent Pale Green	13 sqm per litre	Touch dry: 30 mins Hard dry: 2 hours	
Luminous Foundation Base	Wood, Metal, Masonry	500ml 2.5 litre.	White	13 sqm per litre	Touch dry: 30 mins Hard dry: 2 hours	Matt
Luminous Clear Protective	Wood, Metal, Masonry	500ml 2.5 litre.	Clear	14 sqm per litre	Touch dry: 45 mins Hard dry: 4 hours	Gloss
Suregrip Anti-slip Floor paint	Wood, Metal, Concrete, GRP	1 litre, 2.5 litre, 5 litre.	Blue, Red, Green, Black, Grey, White, Light Grey, Safety Yellow	6-10 sqm per litre	Touch dry: 5 hours Hard dry: 24 hours	Aggregated
Line Marking Aerosols	Tarmac, Wood, Metal, Concrete	750ml Aerosol (packed in 6's).	White, Yellow, Black, Red, Blue, Green	60-100 metres of long lines per can	Touch dry: 15 mins Hard dry: 2 hours	Matt
Anti-slip Tapes and Treads	Wood, Metal, Concrete	Tapes: 50mm wide x 18.2 metres long Treads: 610mm x 150mm	Tapes: Red, Black, Grey, White, Black/Yellow Hazard Stripe, Clear, Luminescent Treads: Black	N/A	N/A	Rough Anti-slip



Ellenshaw Works, Lockwood Street, Hull, HU2 0HN, UK Tel: +44 (0)1482 328 053 Fax: +44 (0)1482 219 266 Email: info@coo-var.co.uk

www.coo-var.co.uk

#### TECHNICAL & SPECIFICATION SERVICE

For full application details or technical and health & safety information, please read the relevant product data sheets which are available from our sales office and are downloadable from our website www.coo-var.co.uk.

The Coo-Var Technical Services Department can provide a wide range of services, information and back-up to support our customers and end users.

To arrange for a site visit and specification, please contact us.



# Safety and Security









**Problem Solving Products** for the 21st Century



# ESSENTIAL PROBLEM SOLVING SOLUTIONS FROM COO-VAR

### **Graffiti Protection**

### P101 Anti-graffiti Coating

P101 is a two pack, clear polyurethane coating which provides a highly graffiti-resistant finish.

This coating has good chemical resistance making it easy to clean and durable. Will not fade or yellow when exposed to high levels of Ultra Violet light, or support the growth of fungus.

Dries to a clear, gloss finish. Is particularly suitable for outdoor use but can also be used indoors.

P101 is suitable for many surfaces, but is not for use over conventional solvent based paints. P101 Brushwash/Thinners also available.

## **WB101** Anti-graffiti Coating

WB101 is a two pack, water based polyurethane coating which acts as a sealer (reducing absorbency),

allowing the removal of graffiti with solvent based products (see Graffiti Removers) and easy cleaning.

Being water based, this coating is low odour sometimes important within indoor environments e.g. hospitals, schools and other public buildings.

#### Anti-graffiti Kit also available.

An easy, no fuss way to get all you need to create your graffiti resistant surface. Kit contains: WB101 2.5L 2 pack unit, paint brush, mixer paddle, gloves and instructions.

> Water **Based**

The Safety and Security range is specially designed to offer a variety of easy to use problem solving products.

Coo-Var have over 100 years experience manufacturing specialist paints, including a range of anti-graffiti, anti-climb and anti-slip

This brochure takes you through Coo-Var's range of safety and security products, which

**GP101 Graffiti & Flyposting** 

applications they are suitable for, their benefits and their technical information (back page).

Not sure which to use for your specific job? At any point in your decision or even after the coating is applied, you can call Coo-Var Technical Services to get advice and to answer any questions you may have - 01482 328053.

#### Vandalene **Anti-climb Paint**

A thick, non-drying product of a sticky nature. Designed to create a slippery surface so that indruders cannot get a grip and will become coated. Ideal for use above head height on gutters, pipes, walls, roofs, window sills etc.

PREVENT ACCIDENTAL DAMAGE -Warning signs available.









**CLEAN OFF** 

**GRAFFITI** 

**USING ONLY** 

WATER

# Glocote Fluorescent Paint

High visability paint which helps draw attention/ identify hazards or safety equipment such as fire extinguishers, skips and exits. For use in daylight or under lights at night.









#### **Glocote Foundation**

#### **Glocote Protective**

A clear coating ideal to cover exterior use of Glocote paint to protect from weathering/extreme wear.

Use under Glocote Paint to give a white base.

#### **Luminous Paint**

This coating glows in the dark for a limited time when lights fail. Ideal for use around exits, edges of steps. Especially useful in buildings with large amounts of people.

#### **Luminous Foundation Base**

Use under Luminous Paint to give a white base.

#### **Luminous Clear Protective**

A clear coating for use over Luminous paint to protect from weathering/extreme wear.

Water Based

## SUREGRIP Suregrip Anti-slip Safety Floor Paint

Suitable for interior & exterior use on ramps, walkways, stairwells, around machinery and most areas where slip resistance is required. Suitable for foot and light truck traffic on wood, metal, masonry, concrete, brick and GRP. Available in 8 colours.

**HELP PREVENT ACCIDENTS** 

#### **Line Marking** Aerosols & Stencils

The

**SIMPLE** 

Solution

Line Marking Aerosols are a fast easy way to mark out lines. When used in conjunction with stencils, they are ideal to identify and mark safety or critical areas. Specific words and phrases are available or the alphabet with numbers to make your

NO PARKING RESERVED DANGER EXIT ONLY ENTRANCE VISITORS STAFF ONLY FIRE EXIT KEEP CLEAR DISABLED IN/OUT

Available in various sizes



### Anti-slip Tapes & Treads also available NOTE: Always read the instructions as well as health & safety information before applying any coating.





#### • Save money - no need to buy solvents PLUS inhouse cleaners can wash off graffiti using only water

**GP101 Sealer Coat** 

• Little 'ghosting' remains

**Protection System** 

This single pack system is a clear

coating which offers long term

protection against both graffiti

and flyposters.

The Sealer Coat is recommended before GP101 Graffiti Protection System is applied on porous surfaces.

• Fast drying – apply two coats in the same day

• Flyposters do not stick properly and just peel off

• Can be applied to rough or smooth surfaces

A transparent sealer which offers excellent water and mildew resistance on porous surfaces, is acrylic and free of volatile organic solvents. This results in it being low odour, non flammable and low toxicity.

Can also be used to minimise the darkening of sandstone and other natural stone products.

#### Graffiti Removers

For use before you apply a graffiti protection coating (to remove current graffiti) and after use once graffiti is applied over the coating.

- Liquid Aerosol tough on graffiti
- Wipes for easy removal of small amounts of graffiti

NOTE: Not for use with GP101