

# COO-VAR®

## PAINTS, PRIMERS AND SPECIALISED COATINGS

### SAFETY DATA SHEET

#### 132/Q265 - FLOORPACK - HARDENER

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** 132/Q265 - FLOORPACK - HARDENER  
**Product number** 132/Q265/1 - HARDENER  
**UFI** UFI: Y2GP-C2G1-V00R-Y0NV

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** HARDENER FOR TWO COMPONENT Crack and hole filler

##### 1.3. Details of the supplier of the safety data sheet

|                       |  |  |
|-----------------------|--|--|
| <b>Supplier</b>       | COO-VAR<br>Lockwood Street<br>HULL UK<br>HU2 0HN<br>+441482328053 (T)<br>+441482219266 (F)<br>info@coo-var.co.uk                   | TEAL & MACKRILL EU B.V.<br>Zandvoortstraat 69<br>1976 BN IJMUIDEN<br>THE NETHERLANDS<br>+441482328053 (T)<br>+441482219266 (F)<br>info@coo-var.co.uk |
| <b>Contact person</b> | Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above   |  |
| <b>Manufacturer</b>   | TEAL & MACKRILL LIMITED<br>LOCKWOOD STREET<br>HULL<br>HU2 0HN<br>+44(0)1482 320194(T)<br>+44(0)1482 219266(F)<br>info@teamac.co.uk |  |

##### 1.4. Emergency telephone number

**Emergency telephone** +44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

**SDS No.** 10835

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Not Classified  
**Health hazards** Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317  
**Environmental hazards** Not Classified

**Human health** The product contains a small amount of sensitising substance. May cause skin sensitisation or allergic reactions in sensitive individuals.

## 132/Q265 - FLOORPACK - HARDENER

**Physicochemical** When handled correctly, undamaged units represent no danger.

### 2.2. Label elements

#### Hazard pictograms



**Signal word** Warning

**Hazard statements** H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.

**Precautionary statements** P102 Keep out of reach of children.  
P101 If medical advice is needed, have product container or label at hand.  
P261 Avoid breathing vapour/ spray.  
P262 Do not get in eyes, on skin, or on clothing.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P332+P313 If skin irritation occurs: Get medical advice/ attention.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 If eye irritation persists: Get medical advice/ attention.  
P501 Dispose of contents/ container in accordance with national regulations.

**Contains** 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE, m-phenylenebis(methylamine), 4-4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)

**Supplementary precautionary statements** P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide or dry powder to extinguish.  
P403+P235 Store in a well-ventilated place. Keep cool.

### 2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

|                         |  |
|-------------------------|--|
| <b>Silica sand fine</b> | <b>60-100%</b>                                   |
| CAS number: —           |  |
| <b>Classification</b>   | <b>Classification (67/548/EEC or 1999/45/EC)</b> |
| Not Classified          | -  |

**132/Q265 - FLOORPACK - HARDENER**

|  |  |  |
|--|--|--|
| <b>Benzyl Alcohol</b> <span style="float: right;"><b>1-5%</b></span>   |  |  |
| CAS number: 100-51-6   | EC number: 202-859-9   | REACH registration number: 01-2119492630-38-XXXX |
| <b>Classification</b><br>Acute Tox. 4 - H302<br>Acute Tox. 4 - H332<br>Eye Irrit. 2 - H319   |  |  |
| <b>3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE</b> <span style="float: right;"><b>1-5%</b></span>   |  |  |
| CAS number: 2855-13-2  | EC number: 220-666-8   |  |
| <b>Classification</b><br>Acute Tox. 4 - H302<br>Acute Tox. 4 - H312<br>Skin Corr. 1B - H314<br>Eye Dam. 1 - H318<br>Skin Sens. 1 - H317<br>Aquatic Chronic 3 - H412                                  | <b>Classification (67/548/EEC or 1999/45/EC)</b><br>C;R34 Xn;R21/22 R43 R52/53 |  |
| <b>m-phenylenebis(methylamine)</b> <span style="float: right;"><b>1-5%</b></span>  |  |  |
| CAS number: 1477-55-0  | EC number: 216-032-5   | REACH registration number: 01-2119480150-50      |
| <b>Classification</b><br>Acute Tox. 4 - H302<br>Acute Tox. 4 - H332<br>Skin Corr. 1B - H314<br>Skin Sens. 1 - H317<br>Aquatic Chronic 3 - H412   |  |  |
| <b>SALICYLIC ACID</b> <span style="float: right;"><b>&lt;1%</b></span>   |  |  |
| CAS number: 69-72-7  | EC number: 200-712-3   | REACH registration number: 01-2119486984-17-XXXX |
| <b>Classification</b><br>Acute Tox. 4 - H302<br>Eye Dam. 1 - H318<br>Repr. 2 - H361  | <b>Classification (67/548/EEC or 1999/45/EC)</b><br>Xn;R22. Xi;R37/38,R41.     |  |
| <b>4-4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)</b> <span style="float: right;"><b>&lt;1%</b></span> |  |  |
| CAS number: 113930-69-1  | EC number: 500-302-7   |  |
| <b>Classification</b><br>Acute Tox. 4 - H302<br>Skin Sens. 1 - H317<br>Aquatic Chronic 2 - H411  |  |  |

## 132/Q265 - FLOORPACK - HARDENER

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

|                                   |   |
|-----------------------------------|---|
| <b>General information</b>        | Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.  |
| <b>Inhalation</b>                 | Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.  |
| <b>Ingestion</b>                  | Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. |
| <b>Skin contact</b>               | Rinse with water.   |
| <b>Eye contact</b>                | Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.   |
| <b>Protection of first aiders</b> | First aid personnel should wear appropriate protective equipment during any rescue.   |

#### 4.2. Most important symptoms and effects, both acute and delayed

|                            |   |
|----------------------------|---|
| <b>General information</b> | See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.                |
| <b>Inhalation</b>          | Prolonged inhalation of high concentrations may damage respiratory system. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic. |
| <b>Ingestion</b>           | Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.                                       |
| <b>Skin contact</b>        | Prolonged contact may cause dryness of the skin. Discoloration of the skin.   |
| <b>Eye contact</b>         | May cause temporary eye irritation.   |

#### 4.3. Indication of any immediate medical attention and special treatment needed

|                             |                        |
|-----------------------------|------------------------|
| <b>Notes for the doctor</b> | Treat symptomatically. |
|-----------------------------|------------------------|

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

|                                       |  |
|---------------------------------------|--|
| <b>Suitable extinguishing media</b>   | The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. |
| <b>Unsuitable extinguishing media</b> | Do not use water jet as an extinguisher, as this will spread the fire.   |

#### 5.2. Special hazards arising from the substance or mixture

|                                      |  |
|--------------------------------------|--|
| <b>Specific hazards</b>              | Containers can burst violently or explode when heated, due to excessive pressure build-up.                   |
| <b>Hazardous combustion products</b> | Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. |

## 132/Q265 - FLOORPACK - HARDENER

### 5.3. Advice for firefighters

#### **Protective actions during firefighting**

Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak.

#### **Special protective equipment for firefighters**

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### **Personal precautions**

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material.

### 6.2. Environmental precautions

#### **Environmental precautions**

Immiscible with water. Aquatic toxicity is unlikely to occur. However, large or frequent spills may have hazardous effects on the environment. Absorb spillage with non-combustible, absorbent material.

### 6.3. Methods and material for containment and cleaning up

#### **Methods for cleaning up**

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Neutralise with acid. Caution. May generate heat. Following dilution and neutralisation, discharge to the sewer with plenty of water may be permitted. The requirements of the local water authority must be complied with if contaminated water is flushed directly to the sewer. For waste disposal, see Section 13.

### 6.4. Reference to other sections

#### **Reference to other sections**

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### **Usage precautions**

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment.

#### **Advice on general occupational hygiene**

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

## 132/Q265 - FLOORPACK - HARDENER

### Storage precautions

Store away from incompatible materials (see Section 10). Store away from the following materials: Acids. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

### Storage class

Acid-reactive storage.

### 7.3. Specific end use(s)

#### Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Silica sand fine

Long-term exposure limit (8-hour TWA): WEL 0.4 mg/m<sup>3</sup> resp.dust

Short-term exposure limit (15-minute): WEL 0.4 mg/m<sup>3</sup> resp.dust

WEL = Workplace Exposure Limit.

#### m-phenylenebis(methylamine) (CAS: 1477-55-0)

##### DNEL

Workers - Dermal; : .033 mg/kg/day

Workers - Inhalation; : 1.2 mg/m<sup>3</sup>

#### 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE (CAS: 2855-13-2)

##### DNEL

Professional - Inhalation; : 20.1 mg/m<sup>3</sup>

##### PNEC

Professional - Fresh water; 0.06 mg/l

Professional - marine water; 0.006 mg/l

#### SALICYLIC ACID (CAS: 69-72-7)

##### PNEC

Fresh water; 0.2 mg/l

marine water; 0.02 mg/l

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

#### Personal protection

Unprotected persons should be kept away from treated areas.

## 132/Q265 - FLOORPACK - HARDENER

|  |  |
|--|--|
| <b>Eye/face protection</b>             | Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.   |
| <b>Hand protection</b>                 | To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturers' performance data suggest that the optimum glove for use should be: Wear protective gloves made of the following material: Viton rubber (fluoro rubber). Thickness: $\geq 0.7$ mm or Polyvinyl alcohol (PVA). Thickness: $\geq 0.2 - 0.3$ mm or Polyethylene. Thickness: $\geq 0.062$ mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn. |
| <b>Other skin and body protection</b>  | Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.  |
| <b>Hygiene measures</b>                | Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.   |
| <b>Respiratory protection</b>          | Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.  |
| <b>Environmental exposure controls</b> | Keep container tightly sealed when not in use.   |

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|  |   |
|--|---|
| <b>Appearance</b>                      | Granules. Coloured paste.                   |
| <b>Colour</b>                          | Black. Grey.                                |
| <b>Odour</b>                           | Sweetish.                                   |
| <b>Odour threshold</b>                 | Not determined.                             |
| <b>pH</b>                              | Technically not feasible.                   |
| <b>Melting point</b>                   | Not determined.                             |
| <b>Initial boiling point and range</b> | $>150^{\circ}\text{C}$ @ 760 mm Hg          |
| <b>Flash point</b>                     | 28 (approx.) $^{\circ}\text{C}$ Closed cup. |
| <b>Evaporation rate</b>                | Not determined.                             |
| <b>Evaporation factor</b>              | Not determined.                             |

## 132/Q265 - FLOORPACK - HARDENER

|   |                                 |
|---|---------------------------------|
| <b>Upper/lower flammability or explosive limits</b> | : 0.8                           |
| <b>Other flammability</b>                           | Not determined.                 |
| <b>Vapour pressure</b>                              | <0.1 mbar @ °C                  |
| <b>Vapour density</b>                               | heavier than air                |
| <b>Relative density</b>                             | 2.22 @ @ 25 C°C                 |
| <b>Solubility(ies)</b>                              | Immiscible with water           |
| <b>Partition coefficient</b>                        | Not determined.                 |
| <b>Auto-ignition temperature</b>                    | >200°C                          |
| <b>Decomposition Temperature</b>                    | Not determined.                 |
| <b>Viscosity</b>                                    | 400 mPas @ 25 C°C               |
| <b>Explosive properties</b>                         | Not determined.                 |
| <b>Explosive under the influence of a flame</b>     | Not considered to be explosive. |
| <b>Oxidising properties</b>                         | Not determined.                 |

### 9.2. Other information

|                                  |   |
|----------------------------------|---|
| <b>Volatility</b>                | 0   |
| <b>Volatile organic compound</b> | This product contains a maximum VOC content of 0 g/litre. |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

|                   |  |
|-------------------|--|
| <b>Reactivity</b> | See the other subsections of this section for further details. |
|-------------------|--|

### 10.2. Chemical stability

|                  |   |
|------------------|---|
| <b>Stability</b> | Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions. |
|------------------|---|

### 10.3. Possibility of hazardous reactions

|   |   |
|---|---|
| <b>Possibility of hazardous reactions</b> | No potentially hazardous reactions known. |
|---|---|

### 10.4. Conditions to avoid

|                            |  |
|----------------------------|--|
| <b>Conditions to avoid</b> | Avoid excessive heat for prolonged periods of time. Containers can burst violently or explode when heated, due to excessive pressure build-up. |
|----------------------------|--|

### 10.5. Incompatible materials

|                           |   |
|---------------------------|---|
| <b>Materials to avoid</b> | Acid anhydrides. Acids. Phenols, cresols. |
|---------------------------|---|

### 10.6. Hazardous decomposition products

|   |  |
|---|--|
| <b>Hazardous decomposition products</b> | Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. |
|---|--|

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral



**132/Q265 - FLOORPACK - HARDENER**

**ATE oral (mg/kg)** 10,866.31

**Acute toxicity - dermal**

**ATE dermal (mg/kg)** 54,835.49

**Acute toxicity - inhalation**

**ATE inhalation (vapours mg/l)** 223.82

**ATE inhalation (dusts/mists mg/l)** 66.8

**Skin corrosion/irritation**

**Skin corrosion/irritation** Causes severe burns.

**Serious eye damage/irritation**

**Serious eye damage/irritation** Causes serious eye damage.

**Skin sensitisation**

**Skin sensitisation** May cause an allergic skin reaction.

**Germ cell mutagenicity**

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Carcinogenicity**

**Carcinogenicity** Based on available data the classification criteria are not met.

**Reproductive toxicity**

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Based on available data the classification criteria are not met.

**Specific target organ toxicity - single exposure**

**STOT - single exposure** Based on available data the classification criteria are not met.

**Specific target organ toxicity - repeated exposure**

**STOT - repeated exposure** Based on available data the classification criteria are not met.

**Aspiration hazard**

**Aspiration hazard** Based on available data the classification criteria are not met.

**Toxicological information on ingredients.****Benzyl Alcohol****Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 1,620.0

**Species** Rat

**ATE oral (mg/kg)** 1,620.0

**Acute toxicity - inhalation**

**ATE inhalation (vapours mg/l)** 11.0

**3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE****Acute toxicity - dermal**

**132/Q265 - FLOORPACK - HARDENER**

**Acute toxicity dermal (LD<sub>50</sub> 1,840.0 mg/kg)**

**Species** Rat

**m-phenylenebis(methylamine)****Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub> 930.0 mg/kg)**

**Species** Rat

**ATE oral (mg/kg)** 930.0

**Acute toxicity - dermal**

**Acute toxicity dermal (LD<sub>50</sub> 3,100.0 mg/kg)**

**Species** Rat

**ATE dermal (mg/kg)** 3,100.0

**Acute toxicity - inhalation**

**Acute toxicity inhalation (LC<sub>50</sub> dust/mist mg/l)** 1.34

**Species** Rat

**ATE inhalation (dusts/mists mg/l)** 1.34

**Skin contact** Irritating to skin. May cause sensitisation by skin contact.

**Eye contact** Irritation of eyes and mucous membranes. Risk of serious damage to eyes.

**4-4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)****Acute toxicity - oral**

**ATE oral (mg/kg)** 500.0

**SECTION 12: Ecological information**

**Ecotoxicity** Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

**12.1. Toxicity**

**Toxicity** Based on available data the classification criteria are not met.

**Ecological information on ingredients.****3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE****Acute aquatic toxicity**

**Acute toxicity - fish** LC50, 96 hours: 110 mg/l, Brachydanio rerio (Zebra Fish)

## 132/Q265 - FLOORPACK - HARDENER

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 23 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** EC<sub>50</sub>, 72 hours: 50 mg/l, Scenedesmus subspicatus

### m-phenylenebis(methylamine)

#### Acute aquatic toxicity

**Acute toxicity - fish** LC<sub>50</sub>, > 96 hours: 100 mg/l, Brachydanio rerio (Zebra Fish)  
LC<sub>50</sub>, > 96 hours: 100 mg/l, Oncorhynchus mykiss (Rainbow trout)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 16 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** EC<sub>50</sub>, 72 hours: 12 mg/l, Scenedesmus subspicatus  
IC<sub>50</sub>, 72 hours: mg/l, Algae  
EC<sub>50</sub>, 72 hours: 20.3 mg/l, Selenastrum capricornutum

#### 12.2. Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not determined.

#### Ecological information on ingredients.

### m-phenylenebis(methylamine)

**Bioaccumulative potential** BCF: 2.69134803,

**Partition coefficient** log Pow: 0.18

#### 12.4. Mobility in soil

**Mobility** The product is insoluble in water.

#### 12.5. Results of PBT and vPvB assessment

#### 12.6. Other adverse effects

**Other adverse effects** None known.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

**General information** The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

## 132/Q265 - FLOORPACK - HARDENER

|                         |   |
|-------------------------|---|
| <b>Disposal methods</b> | Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible.  |
| <b>Waste class</b>      | Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging). Wear protective clothing during disposal operations. If disposal is by waste contractor, make sure that he has sufficient information and that waste containers are properly labelled. Ideally this component should be mixed with the appropriate resin base and allowed to react fully producing a solid non hazardous waste. |

### SECTION 14: Transport information

**General** For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

#### 14.1. UN number

|                  |      |
|------------------|------|
| UN No. (ADR/RID) | 3066 |
| UN No. (IMDG)    | 3066 |
| UN No. (ICAO)    | 3066 |

#### 14.2. UN proper shipping name

|                                |                        |
|--------------------------------|------------------------|
| Proper shipping name (ADR/RID) | PAINT RELATED MATERIAL |
| Proper shipping name (IMDG)    | PAINT RELATED MATERIAL |
| Proper shipping name (ICAO)    | PAINT RELATED MATERIAL |

#### 14.3. Transport hazard class(es)

|                     |   |
|---------------------|---|
| ADR/RID class       | 8 |
| IMDG class          | 8 |
| ICAO class/division | 8 |

#### Transport labels



#### 14.4. Packing group

|                       |     |
|-----------------------|-----|
| ADR/RID packing group | III |
| IMDG packing group    | III |
| ICAO packing group    | III |

#### 14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant**  
No.

#### 14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## 132/Q265 - FLOORPACK - HARDENER

EmS F-A,S-B

Tunnel restriction code (E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78  
and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Commission Regulation (EU) No 2015/830 of 28 May 2015.  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### Inventories

#### **EU - EINECS/ELINCS**

None of the ingredients are listed or exempt.

## SECTION 16: Other information

**Abbreviations and acronyms used in the safety data sheet** ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.  
RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.  
IATA: International Air Transport Association.  
ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.  
IMDG: International Maritime Dangerous Goods.  
CAS: Chemical Abstracts Service.  
ATE: Acute Toxicity Estimate.  
LC<sub>50</sub>: Lethal Concentration to 50 % of a test population.  
LD<sub>50</sub>: Lethal Dose to 50% of a test population (Median Lethal Dose).  
EC<sub>50</sub>: 50% of maximal Effective Concentration.  
PBT: Persistent, Bioaccumulative and Toxic substance.  
vPvB: Very Persistent and Very Bioaccumulative.

**132/Q265 - FLOORPACK - HARDENER**

|  |  |
|--|--|
| <b>Classification abbreviations and acronyms</b> | <p>Acute Tox. = Acute toxicity<br/>         Aquatic Acute = Hazardous to the aquatic environment (acute)<br/>         Aquatic Chronic = Hazardous to the aquatic environment (chronic)<br/>         Asp. Tox. = Aspiration hazard<br/>         Carc. = Carcinogenicity<br/>         Eye Dam. = Serious eye damage<br/>         Eye Irrit. = Eye irritation<br/>         Flam. Liq. = Flammable liquid<br/>         Repr. = Reproductive toxicity<br/>         Resp. Sens. = Respiratory sensitisation<br/>         Skin Corr. = Skin corrosion<br/>         Skin Irrit. = Skin irritation<br/>         Skin Sens. = Skin sensitisation<br/>         STOT RE = Specific target organ toxicity-repeated exposure<br/>         STOT SE = Specific target organ toxicity-single exposure</p> |
| <b>Training advice</b>                           | Read and follow manufacturer's recommendations. Only trained personnel should use this material.   |
| <b>Revision comments</b>                         | Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Revisions to Sections (2),(3),(8),(15), and (16) - re-classification of resin components. Unique Formula Identifier (UFI) added Addition of EU supplier information   |
| <b>Issued by</b>                                 | Technical Dept. (P.E.)   |
| <b>Revision date</b>                             | 17/03/2021   |
| <b>Revision</b>                                  | 5.3  |
| <b>Supersedes date</b>                           | 16/12/2020   |
| <b>SDS number</b>                                | 10835  |
| <b>SDS status</b>                                | Approved.  |
| <b>Hazard statements in full</b>                 | <p>H302 Harmful if swallowed.<br/>         H312 Harmful in contact with skin.<br/>         H314 Causes severe skin burns and eye damage.<br/>         H315 Causes skin irritation.<br/>         H317 May cause an allergic skin reaction.<br/>         H318 Causes serious eye damage.<br/>         H319 Causes serious eye irritation.<br/>         H332 Harmful if inhaled.<br/>         H361 Suspected of damaging fertility or the unborn child.<br/>         H411 Toxic to aquatic life with long lasting effects.<br/>         H412 Harmful to aquatic life with long lasting effects.</p>   |
| <b>Signature</b>                                 | Initials .....   |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.