

COO-VAR®

PAINTS, PRIMERS AND SPECIALISED COATINGS

SAFETY DATA SHEET

138/W224 - GUARD-COAT BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	138/W224 - GUARD-COAT BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW
Product number	138/W224/65/2/1/15/766/776
UFI	UFI: ASKP-4254-2000-EPQN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	BASE FOR TWO COMPONENT FLOOR COATING
-----------------	--------------------------------------

1.3. Details of the supplier of the safety data sheet

Supplier	COO-VAR Lockwood Street HULL UK HU2 0HN +441482328053 (T) +441482219266 (F) info@coo-var.co.uk	TEAL & MACKRILL EU B.V. Zandvoortstraat 69 1976 BN IJMUIDEN THE NETHERLANDS +441482328053 (T) +441482219266 (F) info@coo-var.co.uk
Contact person	Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above	
Manufacturer	TEAL & MACKRILL LIMITED LOCKWOOD STREET HULL HU2 0HN +44(0)1482 320194(T) +44(0)1482 219266(F) info@teamac.co.uk	

1.4. Emergency telephone number

Emergency telephone	+44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)
SDS No.	11274

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Not Classified
Health hazards	Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317
Environmental hazards	Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Human health	The product contains a small amount of sensitising substance. May cause skin sensitisation or allergic reactions in sensitive individuals.
--------------	--

138/W224 - GUARD-COAT BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW

Physicochemical When handled correctly, undamaged units represent no danger.

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements
 P102 Keep out of reach of children.
 P101 If medical advice is needed, have product container or label at hand.
 P270 Do not eat, drink or smoke when using this product.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label information
 Contains a biocidal product
 May produce an allergic reaction.
 EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains
 FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL, OXIRANE, MONO [(C12-14- ALKYL OXY)METHYL] DERIVS

Supplementary precautionary statements
 P261 Avoid breathing vapour/ spray.
 P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide or dry powder to extinguish.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

138/W224 - GUARD-COAT BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL			10-30%
CAS number: 9003-36-5	EC number: 500-006-8	REACH registration number: 01-2119454392-40-0003	
Classification		Classification (67/548/EEC or 1999/45/EC)	
Skin Irrit. 2 - H315		Xi;R38. N;R51/53. R43.	
Skin Sens. 1 - H317			
Aquatic Chronic 2 - H411			
OXIRANE, MONO [(C12-14- ALKYL OXY)METHYL] DERIVS			5-10%
CAS number: 68609-97-2	REACH registration number: 01-2119485289-22-0005		
Classification		Classification (67/548/EEC or 1999/45/EC)	
Skin Irrit. 2 - H315		R43 Xi;R38	
Skin Sens. 1 - H317			
Titanium Dioxide			1-5%
CAS number: 13463-67-7	EC number: 236-675-5	REACH registration number: 01-2119489379-17-xxxx	
Classification		Classification (67/548/EEC or 1999/45/EC)	
Carc. 2 - H351		-	
Silver chloride (soluble silver)			<1%
CAS number: 7783-90-6	EC number: 232-033-3		
M factor (Acute) = 1000	M factor (Chronic) = 100		
Classification		Classification (67/548/EEC or 1999/45/EC)	
Aquatic Acute 1 - H400		N;R50.	
Aquatic Chronic 1 - H410			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1% or more of titanium dioxide which is in the form of or incorporated into particles with an aerodynamic diameter of less than or equal to 10µm.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.

138/W224 - GUARD-COAT BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW

Ingestion	Give a few small glasses of water or milk to drink. Never give anything by mouth to an unconscious person. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Rinse immediately with plenty of water. Remove contaminated clothing. Get medical attention if irritation persists after washing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

4.2. Most important symptoms and effects, both acute and delayed

General information Get medical attention promptly if symptoms occur after washing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Non flammable at room temperature, but will burn. Use fire-extinguishing media suitable for the surrounding fire. Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Containers close to fire should be removed or cooled with water.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

138/W224 - GUARD-COAT BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW

Usage precautions Avoid inhalation of vapours. Avoid spilling, skin and eye contact. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product. For products sold by weight refer to the guide net weight indicated on the container. Allowance will have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly closed original container in a dry, cool and well-ventilated place. Store in closed original container at temperatures between 5°C and 25°C. Protect from freezing and direct sunlight. Keep containers upright.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Titanium Dioxide

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

WEL = Workplace Exposure Limit.

C.I. Pigment Red 101 (CAS: 1309-37-1)

DNEL Industry - Inhalation; Long term local effects: 3 respirable mg/m³
Industry - Inhalation; Long term local effects: 10 Inhalable mg/m³

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL (CAS: 9003-36-5)

DNEL Workers - Inhalation; Long term systemic effects: 29.39 mg/kg
Workers - Dermal; Long term systemic effects: 104.15 mg/kg/day
General population - Inhalation; Long term systemic effects: 8.7 mg/kg
General population - Dermal; Long term systemic effects: 62.5 mg/kg/day
General population - Oral; Long term systemic effects: 6.25 mg/kg/day

Titanium Dioxide (CAS: 13463-67-7)

DNEL Industry - Inhalation; Long term local effects: 10 mg/m³
Consumer - Oral; Long term systemic effects: 700 mg/kg/day

PNEC - Fresh water; 0.184 mg/l
- marine water; 0.0184 mg/l
- Sediment (Freshwater); >=1000 mg/kg
- Sediment (Marinewater); >=100 mg/kg
- Soil; 100 mg/kg
- STP; 100 mg/kg

138/W224 - GUARD-COAT BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Personal protection

Unprotected persons should be kept away from treated areas.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturers' performance data suggest that the optimum glove for use should be: Butyl rubber. Thickness: > 0.5 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. or Nitrile rubber. Thickness: > 0.4 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 240 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

Other skin and body protection

Wear appropriate clothing to prevent reasonably probable skin contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid. Coloured liquid.
Colour	Red.
Odour	Sweetish.
Odour threshold	Not determined.
pH	Technically not feasible.
Melting point	Not determined.
Initial boiling point and range	>150°C @ 760 mm Hg
Flash point	28 (approx.)°C Closed cup.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Upper/lower flammability or explosive limits	: 0.8

138/W224 - GUARD-COAT BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW

Other flammability	Not determined.
Vapour pressure	<0.1 mbar @ °C
Vapour density	heavier than air
Relative density	1.12 @ @ 25°C
Solubility(ies)	Immiscible with water
Partition coefficient	Not determined.
Auto-ignition temperature	>200°C
Decomposition Temperature	Not determined.
Viscosity	0.90 Pas @ 25 C°C
Explosive properties	Not determined.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not determined.

9.2. Other information

Volatile organic compound EU: (cat A/j): 140 g/l 2010. This product contains a maximum VOC content of <1 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not occur

10.4. Conditions to avoid

Conditions to avoid Not known.

10.5. Incompatible materials

Materials to avoid Strong acids. Alkalis - inorganic. Amines. Mercaptans (thiols).

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No data recorded.

General information No specific health hazards known.

Inhalation May cause respiratory system irritation.

138/W224 - GUARD-COAT BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW

Ingestion	Harmful if swallowed. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.
Skin contact	Irritating to skin. May cause sensitisation by skin contact.
Eye contact	Irritating to eyes.
Acute and chronic health hazards	May cause sensitisation by skin contact. Delayed appearance of the complaints and development of hypersensitivity (difficulty breathing, coughing, asthma) are possible.
Route of exposure	Inhalation Skin absorption. Ingestion. Skin and/or eye contact.
Medical considerations	Skin disorders and allergies.

Toxicological information on ingredients.

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,100.0

Species Rat

ATE oral (mg/kg) 2,100.0

Silver chloride (soluble silver)

Toxicological effects No indication of mutagenic effects.

SECTION 12: Ecological information

Ecotoxicity There are no data on the ecotoxicity of this product. The product contains a substance which is very toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

Ecological information on ingredients.

Silver chloride (soluble silver)

Ecotoxicity Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

Ecological information on ingredients.

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: >100 mg/l, Leuciscus idus (Golden orfe)

Acute toxicity - aquatic invertebrates LC₅₀, 96 hours: >100 mg/l, Daphnia magna

Silver chloride (soluble silver)

Acute aquatic toxicity

LE(C)₅₀ 0.0001 < L(E)C₅₀ ≤ 0.001

138/W224 - GUARD-COAT BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW

M factor (Acute)	1000
Acute toxicity - fish	LC ₅₀ , 96 hours: 0.005 g/l mg/l, Fish
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 0.000074 g/l mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC ₅₀ , 72 hours: 0.003 g/l mg/l, Algae
<u>Chronic aquatic toxicity</u>	
M factor (Chronic)	100

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility The product is non-volatile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Avoid the spillage or runoff entering drains, sewers or watercourses. Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered. DO NOT reuse containers containing residual product without commercial cleaning

Waste class When this material, in its liquid state, as supplied, becomes a waste, it is categorised as a hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing residues of the supplied material, are categorised as hazardous waste, with code 08 01 11* (EPOXY BASED LIQUID WASTE). Ideally this component should be mixed with the appropriate hardener and allowed to react fully to produce a solid waste. Neutralised empty packages, are categorised as non-hazardous waste, with code 15 01 02(plastic packaging) or 15 01 04 (metal packaging)

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

14.1. UN number

UN No. (ADR/RID) 3082

UN No. (IMDG) 3082

138/W224 - GUARD-COAT BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW

14.2. UN proper shipping name

Proper shipping name (ADR/RID) Paint

Proper shipping name (IMDG) Paint

Proper shipping name (ICAO) Paint

Proper shipping name (ADN) Paint

14.3. Transport hazard class(es)

ADR/RID class 9

IMDG class 9

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

138/W224 - GUARD-COAT BASE FOR TILE RED, BLACK, WHITE, GREEN, SAFETY RED & YELLOW

Revision comments	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Classification of Titanium Dioxide updated in line with the 14th ATP to CLP.
Issued by	Technical Dept. (N.O.)
Revision date	08/09/2021
Revision	4.0
Supersedes date	28/01/2021
SDS number	11274
SDS status	Approved.
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H351 Suspected of causing cancer. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.
Signature	Initials _____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.