

COO-VAR®

PAINTS, PRIMERS AND SPECIALISED COATINGS

SAFETY DATA SHEET

308/Q271 - DANISH OIL

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 308/Q271 - DANISH OIL

Product number 308/Q271/4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Wood preservation for outdoor use.

1.3. Details of the supplier of the safety data sheet

Supplier COO-VAR
Lockwood Street
Hull
HU2 0HN
+44 (0) 1482 328053(T)
+44 (0) 1482 219266(F)
info@coo-var.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 10710

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards STOT SE 3 - H336 Asp. Tox. 1 - H304

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) N;R51/53. R10,R66,R67.

2.2. Label elements

Pictogram



Signal word

Danger

308/Q271 - DANISH OIL

Hazard statements	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness.
Precautionary statements	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P261 Avoid breathing vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	HYDROCARBONS, C9-C11, <2% AROMATICS, Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARBONS, C9-C11, <2% AROMATICS 30-60%		
CAS number: —	EC number: 919-857-5	REACH registration number: 01-2119463258-33-XXXX
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) Xn;R65. R10,R66,R67.	
Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics 10-30%		
CAS number: 64742-48-9	EC number: 918-481-9	REACH registration number: 01-2119457273-39-0000
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304		

308/Q271 - DANISH OIL

XYLENE		<1%
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-xxxx
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	Classification (67/548/EEC or 1999/45/EC) Xn;R20/21,R65. Xi;R36/37/38. R10.	
Cobalt bis(2-ethylhexanoate)		<1%
CAS number: 136-52-7	EC number: 205-250-6	M factor (Acute) = 1
Classification Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Repr. 2 - H361 Aquatic Acute 1 - H400 Aquatic Chronic 3 - H412	Classification (67/548/EEC or 1999/45/EC) Xn;R22. Xi;R38. N;R51/53. R43.	
ETHYL METHYL KETOXIME - reaction product		<1%
CAS number: 96-29-7	EC number: 202-496-6	
Classification Acute Tox. 4 - H312 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Carc. 2 - H351	Classification (67/548/EEC or 1999/45/EC) Carc. Cat. 3;R40 Xn;R21 R43 Xi;R41	
2-ETHYLHEXANOIC ACID		<1%
CAS number: 149-57-5	EC number: 205-743-6	
Classification Repr. 2 - H361d	Classification (67/548/EEC or 1999/45/EC) Repr. Cat. 3;R63	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.

Inhalation

Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.

Ingestion

DO NOT induce vomiting. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

308/Q271 - DANISH OIL

Skin contact Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information Get medical attention promptly if symptoms occur after washing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases or vapours. FLAMMABLE. Solvent vapours may form explosive mixtures with air.

5.3. Advice for firefighters

Protective actions during firefighting Risk of re-ignition after fire has been extinguished. Cool containers exposed to flames with water until well after the fire is out. Avoid the spillage or runoff entering drains, sewers or watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

308/Q271 - DANISH OIL

Usage precautions

Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists. Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not eat, drink or smoke when using the product. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Keep container tightly closed. Keep containers upright. Store away from the following materials: Oxidising materials. Alkalis. Acids.

Storage class

Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

Usage description

Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

ETHYL METHYL KETOXIME - reaction product

Long-term exposure limit (8-hour TWA): OEL 3 ppm 10 mg/m³

WEL = Workplace Exposure Limit

OEL = Occupational Exposure Limit.

HYDROCARBONS, C9-C11, <2% AROMATICS

DNEL

Consumer - Oral; Long term systemic effects: 300 mg/kg/day
 Industry - Inhalation; Long term systemic effects: 1500 mg/m³
 Industry - Dermal; Long term systemic effects: 300 mg/kg/day
 Consumer - Dermal; Long term systemic effects: 300 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 900 mg/m³

PNEC

No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

308/Q271 - DANISH OIL

Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics (CAS: 64742-48-9)

DNEL	Workers - Inhalation; Long term systemic effects: 1500 mg/m ³
	Workers - Dermal; Long term systemic effects: 300 mg/kg/day
	General population - Inhalation; Long term systemic effects: 900 mg/m ³
	General population - Dermal; Long term systemic effects: 300 mg/kg/day
	General population - Oral; Long term systemic effects: 300 mg/kg/day

XYLENE (CAS: 1330-20-7)

DNEL	Consumer - Oral; Long term systemic effects: 1.6 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 108 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 14.8 mg/m ³
	Industry - Dermal; Long term systemic effects: 180 mg/kg/day
	Industry - Inhalation; Long term systemic effects: 77 mg/m ³
	Industry - Inhalation; Short term local effects: 289 mg/m ³

PNEC	- Fresh water; 0.327 mg/l
	- Marine water; 0.327 mg/l
	- Intermittent release; 0.327 mg/l
	- Sediment (Freshwater); 12.46 mg/kg
	- Sediment (Marinewater); 12.46 mg/kg
	- Soil; 2.31 mg/kg
	- STP; 6.58 mg/kg

Cobalt bis(2-ethylhexanoate) (CAS: 136-52-7)

DNEL	General population - Oral; Long term systemic effects: 0.0276 mg/kg
PNEC	Fresh water; 0.0006 mg/l
	Marine water; 0.00236 mg/l
	STP; 0.37 mg/kg
	Sediment (Freshwater); 9.5 mg/l
	Sediment (Marinewater); 9.5 mg/l
	Soil; 10.9 mg/kg

ETHYL METHYL KETOXIME - reaction product (CAS: 96-29-7)

Ingredient comments	Methyl Ethyl Ketoxime {Butanone Oxime, CAS 96 29 7 } is a reaction product following hydrolysis of the coating with atmospheric moisture.
----------------------------	---

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear chemical splash goggles.

308/Q271 - DANISH OIL

Hand protection	To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Wear protective gloves made of the following material: Nitrile rubber. Thickness: \geq 0.31 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.
Other skin and body protection	Wear appropriate clothing to prevent reasonably probable skin contact.
Hygiene measures	No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.
Respiratory protection	Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. In case of inadequate ventilation use suitable respirator. It is recommended to use respiratory equipment with combination filter, type A2/P2.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid. Clear, yellowish liquid.
Odour	Organic solvents.
Flash point	38°C Closed cup.
Upper/lower flammability or explosive limits	: 0.8
Vapour density	heavier than air
Relative density	0.9 @ @25 C°C
Solubility(ies)	Immiscible with water
Viscosity	124 seconds 3mm ISO cup (ISO 2431) @ °C

9.2. Other information

Volatility	55 (approx.)
Volatile organic compound	This product contains a maximum VOC content of 433 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not determined.
---	-----------------

10.4. Conditions to avoid

308/Q271 - DANISH OIL

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:
Acids. Oxidising agents.

10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation Vapour from this product may be hazardous by inhalation. Vapour may irritate respiratory system/lungs.

Ingestion Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

Skin contact Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause allergic contact eczema. Prolonged or repeated exposure may cause severe irritation.

Eye contact May cause temporary eye irritation.

Acute and chronic health hazards This product has low toxicity. Only large quantities are likely to have adverse effects on human health.

Route of exposure Inhalation Skin absorption. Ingestion. Skin and/or eye contact.

Medical considerations Skin disorders and allergies. Avoid vomiting and stomach flushing because of the risk of aspiration.

Toxicological information

SECTION 12: Ecological Information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is not expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product contains potentially bioaccumulating substances.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

308/Q271 - DANISH OIL

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Avoid the spillage or runoff entering drains, sewers or watercourses.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT
Proper shipping name (IMDG)	PAINT
Proper shipping name (ICAO)	PAINT
Proper shipping name (ADN)	PAINT

14.3. Transport hazard class(es)

ADR/RID class	1263
IMDG class	3
ICAO class/division	3

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

14.5. Environmental hazards

308/Q271 - DANISH OIL**Environmentally hazardous substance/marine pollutant****14.6. Special precautions for user**

EmS F-E, S-E
Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance Workplace Exposure Limits EH40.
 CHIP for everyone HSG228.
 Safety Data Sheets for Substances and Preparations.
 Approved Classification and Labelling Guide (Sixth edition) L131.
 Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830

Issued by Technical Dept. (P.E.)

Revision date 15/05/2018

Revision 7

Supersedes date 14/05/2014

SDS number 10710

SDS status Approved.

308/Q271 - DANISH OIL**Risk phrases in full**

Not classified.
R10 Flammable.
R22 Harmful if swallowed.
R43 May cause sensitisation by skin contact.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62 Possible risk of impaired fertility.
R63 Possible risk of harm to the unborn child.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H361d Suspected of damaging the unborn child.
H400 Very toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Signature

Initials_____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.