

## DANISH OIL

### DESCRIPTION:

Coo-Var Danish Oil is a hard, durable, water resistant seal for the enhancement of interior and exterior wood. Contains tung oil.

### RECOMMENDED USE:

Coo-Var Danish Oil is ideal for use on mahogany, teak and most other timbers. Can be used for kitchen worktops, wooden panels, garden furniture and doors.

### AVAILABILITY:

0.5 litre, 1 litre, 2.5 litre

### FINISH:

Slight gloss

### COLOUR:

Clear

### TYPICAL S.G. (SPECIFIC GRAVITY):

0.9 @ 20 °C

### VOLUME SOLIDS:

47.5%

### WET FILM THICKNESS W.F.T

70 microns

### DRY FILM THICKNESS D.F.T

35 microns

### EXPECTED SPREADING RATE:

14 sq.m / litre

@ 35 microns D.F.T.

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

### TYPICAL VISCOSITY:

124s sec . B3 cup @ 25 °C

### FLASH POINT:

Above 32 °C (closed cup)

### DRYING TIME: @ RECOMMENDED D.F.T

Touch dry: 4 hours @ 20 °C

Hard dry: 8 hours @ 20 °C

Full hardness: 5 to 7 days @ 20 °C

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

### MINIMUM OVERCOATING TIME:

12 hours / overnight

### APPLICATION SPECIAL CONDITIONS:

N/A

### VOC CONTENT:

433 g / litre

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

### APPLICATION DETAILS:

Application N/A  
restrictions

Method: Brush or lint  
free cloth

Thinner Thinners 14 (5%)  
(Max vol):

Nozzle size: N/A

Nozzle N/A  
pressure:

Cleaning Thinners 14  
solvent:

Recoat 12 hours /  
interval: overnight

### SURFACE PREPARATION:

Ensure the surface is clean, dry and free from wax, oil, grease and dirt. Use sandpaper to remove any unwanted old coatings and paints.

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

**"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"**

Ellenshaw Works

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 328053. Fax: +44(0)1482 219266

COO-var

Email: [info@coo-var.co.uk](mailto:info@coo-var.co.uk)

[www.coo-var.co.uk](http://www.coo-var.co.uk)

**DANISH OIL****308/Q271/4**

---

**MIXING INSTRUCTIONS:**

Mix well before use

**APPLICATION CONDITIONS:**

As dictated by normal good painting practice.  
In confined spaces, provide adequate ventilation during application and drying.

**PRECEDING COAT:**

Coo-Var Danish Oil direct to prepared wood.

**SUBSEQUENT COAT:**

Coo-Var Danish Oil

**REMARKS:****HEALTH AND SAFETY:**

See safety data sheet - SDS 10710

**ISSUED:**

20 November 2009

**REVISION:**

0

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, as the conditions of use are beyond our control. This data sheet does not constitute a specification. In case of doubt as to the suitability of the product please contact our Technical Service Department on 01482 328053.

**For further advice contact Coo-Var Technical Services on +44(0)1482 328053**

**The physical constants are subject to normal manufacturing tolerances.**

**"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"**

---

Ellenshaw Works  
Lockwood Street, Hull HU2 0HN  
Tel.: +44(0)1482 328053. Fax: +44(0)1482 219266

COO-var  
Email: [info@coo-var.co.uk](mailto:info@coo-var.co.uk)  
[www.coo-var.co.uk](http://www.coo-var.co.uk)