

LO LINEMARKING PAINT SOLVENT

600/V607/18

DESCRIPTION:

A low aromatic content white spirit.

RECOMMENDED USE:

As a cleaning solvent for brushes and rollers used to apply Coo-Var Low Odour Linemarking paint

AVAILABILITY:

2.5 litre

FINISH:

N/A

COLOUR:

N/A

TYPICAL S.G. (SPECIFIC GRAVITY):

0.77

VOLUME SOLIDS:

N/A

WET FILM THICKNESS W.F.T

DRY FILM THICKNESS D.F.T

EXPECTED SPREADING RATE:

N/A

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

TYPICAL VISCOSITY

FLASH POINT:

38 °C (closed cup)

DRYING TIME: @ RECOMMENDED D.F.T

Touch dry:

Hard dry:

Full hardness:

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

MINIMUM OVERCOATING TIME:

APPLICATION SPECIAL CONDITIONS:

VOC CONTENT:

770 g / litre

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

APPLICATION DETAILS:

Application restrictions

Method

Thinner (Max vol):

Nozzle size:

Nozzle pressure:

Cleaning solvent:

Recoat interval:

SURFACE PREPARATION:

MIXING INSTRUCTIONS:

APPLICATION CONDITIONS:

PRECEDING COAT:

SUBSEQUENT COAT:

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

Ellenshaw Works

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 328053. Fax: +44(0)1482 219266

COO-var

Email: info@coo-var.co.uk

www.coo-var.co.uk

LO LINEMARKING PAINT SOLVENT**600/V607/18**

REMARKS:**HEALTH AND SAFETY:**

See safety data sheet - SDS 11031

ISSUED:

20 May 2009

REVISION:

0

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, since the conditions of use are beyond our control. This data sheet does not constitute a specification. In case of doubt as to the suitability of the product please contact our Technical Service Department.

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

Ellenshaw Works

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 328053. Fax: +44(0)1482 219266

COO-var

Email: info@coo-var.co.ukwww.coo-var.co.uk