

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 13/04/2023 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form Mixture

381/H126 - HAMMERCOTE HAMMERED ENAMEL - ALL COLOURS EXCEPT BLACK Product name

Product code 10932 Paint Type of product Product group : End product

Other means of identification 381/H126/ - all colours

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

No additional information available

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier Distributor

Coo-Var Teal & Mackrill EU B.V. Lockwood Street **Queens Towers** Delflandlaan 1 Hull - East Yorkshire 1062 EA Amsterdam England

T +44 (0)1482 328053 Netherlands

info@coo-var.co.uk T +31 (0)208 004828 info@teamac.co.uk

1.4. Emergency telephone number

: +44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri) **Emergency number**

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226 Acute toxicity (inhalation:dust,mist) Category 4 H332 Skin corrosion/irritation, Category 2 H315 Serious eye damage/eye irritation, Category 2 H319 Specific target organ toxicity - Repeated exposure, Category 2 H373

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

GHS07

GHS08

Signal word (CLP)

: Warning

: XYLENE; ETHYLBENZENE; Xylene isomer mixture (self classification) Contains

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP) : H226 - Flammable liquid and vapour.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H332 - Harmful if inhaled.

H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation. EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

EUH-statements

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
XYLENE substance with national workplace exposure limit(s) (GB)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 REACH-no: 01-2119488216- 32	≥ 10 - < 30	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315
Xylene isomer mixture (self classification) substance with a Community workplace exposure limit	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216- 32	≥ 10 - < 30	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ETHYLBENZENE	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4	≥ 5 – < 10	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373 Asp. Tox. 1, H304
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC-No.: 919-857-5 REACH-no: 01-2119463258- 33	≥ 5 – < 10	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
HYDROCARBONS, C9, AROMATICS substance with national workplace exposure limit(s) (GB)	CAS-No.: 64742-95-6 EC-No.: 918-668-5 REACH-no: 01-2119455851- 35	<1	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
STYRENE	CAS-No.: 100-42-5 EC-No.: 202-851-5 EC Index-No.: 601-026-00-0 REACH-no: 01-2119457861- 32	<1	Flam. Liq. 3, H226 Repr. 2, H361d Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) STOT RE 1, H372 Skin Irrit. 2, H315 Eye Irrit. 2, H319
ETHANOL substance with national workplace exposure limit(s) (GB)	CAS-No.: 64-17-5 EC-No.: 200-578-6 REACH-no: 01-2119457610- 43	< 1	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Dipropylene Glycol Methyl Ether substance with national workplace exposure limit(s) (GB)	CAS-No.: 34590-94-8 EC-No.: 252-104-2 REACH-no: 01-2119450011- 60	< 1	Not classified
METHANOL substance with national workplace exposure limit(s) (GB)	CAS-No.: 67-56-1 EC-No.: 200-659-6	< 1	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Inhalation), H331 (ATE=0.5 mg/l/4h) STOT SE 1, H370
2,6-Di-tert-butyl-p-cresol substance with national workplace exposure limit(s) (GB)	CAS-No.: 128-37-0 EC-No.: 204-881-4 REACH-no: 01-2119565113- 46	< 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Seek medical attention immediately.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

: Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.

First-aid measures after skin contact

First-aid measures after inhalation

First-aid measures after eye contact

: Rinse skin with water/shower.

: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.

Continue rinsing.

First-aid measures after ingestion

: Rinse mouth out with water. If the person is fully conscious, make him/her drink water. Never give an unconscious person anything to drink. Do NOT induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects

The severity of the symptoms described will vary dependant on the concentration and the length of exposure.

Symptoms/effects after inhalation Symptoms/effects after skin contact Symptoms/effects after eye contact

Symptoms/effects after ingestion

: May cause headache, nausea and irritation of respiratory tract. Repeated exposure may cause skin dryness or cracking.

: May cause eye irritation.

: Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2).

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Explosion hazard : Heating may cause a fire or explosion. Hazardous decomposition products in case of fire : Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

Precautionary measures fire : Avoid breathing (dust, vapor, mist, gas). Evacuate area. Cool down the containers exposed

to heat with a water spray.

Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No action shall be taken without appropriate training or involving any personal risk.

6.1.1. For non-emergency personnel

Protective equipment : In case of inadequate ventilation wear respiratory protection. Wear recommended personal protective equipment.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

13/04/2023 (Issue date) GB - en 4/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.3. Methods and material for containment and cleaning up

For containment

: Absorb spilled material with sand or earth. Do not touch or walk on the spilled product.

Collect spillage.

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local

legislation. Clean up any spills as soon as possible, using an absorbent material to collect it.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

Obtain, read and follow all safety instructions before use.

Precautions for safe handling

Wear personal protective equipment. Keep only in original container. Eliminate all ignition sources if safe to do so. Do not handle until all safety precautions have been read and

understood.

Hygiene measures

: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wear personal protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Storage area

: Keep container tightly closed. Store in a well-ventilated place. Keep cool.

: Bund storage facilities to prevent soil and water pollution in the event of spillage.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

METHANOL (67-56-1)			
United Kingdom - Occupational Exposure Limits			
WEL TWA (OEL TWA) [1]	266 mg/m³		
WEL TWA (OEL TWA) [2]	200 ppm		
WEL STEL (OEL STEL)	333 mg/m³		
WEL STEL (OEL STEL) [ppm]	250 ppm		
ETHANOL (64-17-5)			
United Kingdom - Occupational Exposure Limits	United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	1920 mg/m³		
WEL TWA (OEL TWA) [2]	1000 ppm		
Dipropylene Glycol Methyl Ether (34590-94-8)			
United Kingdom - Occupational Exposure Limits			
WEL TWA (OEL TWA) [1]	308 mg/m³		
WEL TWA (OEL TWA) [2]	50 ppm		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HYDROCARBONS, C9, AROMATICS (64742-95-6)		
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	19 mg/m³ (8 hour)	
WEL TWA (OEL TWA) [2]	100 ppm (8 hour)	
XYLENE (1330-20-7)		
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	220 mg/m³	
WEL TWA (OEL TWA) [2]	50 ppm	
WEL STEL (OEL STEL)	441 mg/m³	
WEL STEL (OEL STEL) [ppm]	100 ppm	
2,6-Di-tert-butyl-p-cresol (128-37-0)		
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	10 mg/m ³	
Xylene isomer mixture (self classification) (1330-20-7)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA [ppm]	50 ppm	
IOEL STEL [ppm]	100 ppm	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation. Personal, workplace, environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Ensure control measures are regularly inspected and maintained. In case of insufficient ventilation, wear suitable respiratory equipment.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.2. Skin protection

Hand protection:

Protective gloves against chemicals (EN 374). As a general principal, exposure should be managed by means other than the provision of protective gloves. Permeation time: minimum >480min long term exposure; material / thickness [mm]: The breakthrough time of the selected gloves must be greater than the intended use period.

Other skin protection

Materials for protective clothing:

Use protective clothing. protective footwear

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Consumer exposure controls:

Do not exceed the occupational exposure limits (OEL).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Various colours. : Viscous liquid. Appearance Odour : Not available Odour threshold : Not available Melting point : Not available Freezing point : Not available Boiling point : Not available Flammability : Not available Explosive limits : Not available Lower explosion limit : Not available Upper explosion limit : Not available

Flash point : 25C approximately °C OC (Open cup).

Auto-ignition temperature : Not available Decomposition temperature : Not available

pH : Technically not feasible.

Viscosity, kinematic : > 20.5 mm²/s
Viscosity, dynamic : 2.7 – 3.3 P @ 25°C
Solubility : Not available
Partition coefficient n-octanol/water (Log Kow) : Not available
Vapour pressure : Not available
Vapour pressure at 50°C : Not available
Density : Not available

Relative density : $0.95 - 0.99 \text{ g/ml} @ 20^{\circ}\text{C}$

Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : < 495 g/l

13/04/2023 (Issue date) GB - en 7/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

381/H126 - HAMMERCOTE HAMMERED ENAMEL - ALL COLOURS EXCEPT BLACK

ATE CLP (dust,mist) 3.773 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

pH: Technically not feasible.

HYDROCARBONS, C9, AROMATICS (64742-95-6)

pH Not available.

Serious eye damage/irritation : Causes serious eye irritation.

pH: Technically not feasible.

HYDROCARBONS, C9, AROMATICS (64742-95-6)

pH Not available.

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

METHANOL (67-56-1)

STOT-single exposure Causes damage to organs.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

STOT-single exposure May cause drowsiness or dizziness.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HYDROCARBONS, C9, AROMATICS (64742-95-6)			
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.		
Xylene isomer mixture (self classification) (13	Xylene isomer mixture (self classification) (1330-20-7)		
STOT-single exposure	May cause respiratory irritation.		
STOT-repeated exposure :	May cause damage to organs through prolonged or repeated exposure.		
STYRENE (100-42-5)			
STOT-repeated exposure	Causes damage to organs (hearing organs) through prolonged or repeated exposure.		
ETHYLBENZENE (100-41-4)			
STOT-repeated exposure	May cause damage to organs (hearing organs) through prolonged or repeated exposure.		
Xylene isomer mixture (self classification) (13	30-20-7)		
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.		
Aspiration hazard :	Not classified		
381/H126 - HAMMERCOTE HAMMERED ENAM	IEL - ALL COLOURS EXCEPT BLACK		
Viscosity, kinematic	> 20.5 mm²/s		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Viscosity, kinematic	≤ 20.5 mm²/s		

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

Not rapidly degradable

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

Additional information

European List of Waste (LoW) code

HP Code

- : Do not discharge into drains or rivers.
- : an approved waste disposal plant.
- : Handle empty containers with care because residual vapours are flammable.
- : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

15 01 02 - plastic packaging

15 01 04 - metallic packaging

: HP3 - "Flammable:"

- flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
- flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air:
- flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
- flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
- water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
- HP5 "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.
- HP6 "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.
- HP4 "Irritant skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID n	14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263	
14.2. UN proper shippin	g name				
PAINT	PAINT	Paint	PAINT	PAINT	
Transport document descr	iption				
UN 1263 PAINT, 3, III, (D/E)	UN 1263 PAINT, 3, III	UN 1263 Paint, 3, III	UN 1263 PAINT, 3, III	UN 1263 PAINT, 3, III	
14.3. Transport hazard o	class(es)				
3	3	3	3	3	
3	3	3	3	3	
14.4. Packing group	14.4. Packing group				
III	III	III	III	III	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1

Special provisions (ADR) : 163, 367, 650

Limited quantities (ADR) : 5l Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T2
Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30

Orange plates : 30

30 1263

Tunnel restriction code (ADR) : D/E EAC code : •3Y

Transport by sea

Special provisions (IMDG) : 163, 223, 367, 955

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 : P001, LP01 Packing instructions (IMDG) : PP1 Special packing provisions (IMDG) IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T2 Tank special provisions (IMDG) : TP1, TP29 EmS-No. (Fire) : F-E EmS-No. (Spillage) : S-E Stowage category (IMDG)

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L

Special provisions (IATA) : A3, A72, A192

ERG code (IATA) : 3L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Inland waterway transport

Classification code (ADN) : F1

Special provisions (ADN) : 163, 367, 650

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01

Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1

Special provisions (RID) : 163, 367, 650

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T2
Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : < 495 g/l

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors) Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:		
CAS-No.	Chemical Abstract Service number	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ATE	Acute Toxicity Estimate	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
DNEL	Derived-No Effect Level	
IATA	International Air Transport Association	
LC50	Median lethal concentration	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006	
SDS	Safety Data Sheet	
VOC	Volatile Organic Compounds	

Full text of H- and EUH-statements:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH066	Repeated exposure may cause skin dryness or cracking.	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUI	H-statements:
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 1	Specific target organ toxicity – single exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.