

# COO-VAR®

## PAINTS, PRIMERS AND SPECIALISED COATINGS

### SAFETY DATA SHEET

#### 317/V604 - PATENT KNOTTING

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** 317/V604 - PATENT KNOTTING  
**Product number** 317/V604/13  
**UFI** UFI: 8THP-G290-000M-6UA5

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** As a treatment for resinous knots in wood

##### 1.3. Details of the supplier of the safety data sheet

<b>Supplier</b>	COO-VAR Lockwood Street HULL UK HU2 0HN +441482328053 (T) +441482219266 (F) info@coo-var.co.uk	TEAL & MACKRILL EU B.V. Zandvoortstraat 69 1976 BN IJMUIDEN THE NETHERLANDS +441482328053 (T) +441482219266 (F) info@coo-var.co.uk
<b>Contact person</b>	Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above	
<b>Manufacturer</b>	TEAL & MACKRILL LIMITED LOCKWOOD STREET HULL HU2 0HN +44(0)1482 320194(T) +44(0)1482 219266(F) info@teamac.co.uk	

##### 1.4. Emergency telephone number

**Emergency telephone** +44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

**SDS No.** 10759

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Flam. Liq. 2 - H225  
**Health hazards** Eye Irrit. 2 - H319 STOT SE 3 - H336  
**Environmental hazards** Not Classified

**Classification (67/548/EEC or 1999/45/EC)** Xi;R36. F;R11. R67.

## 317/V604 - PATENT KNOTTING

### 2.2. Label elements

#### Hazard pictograms



#### Signal word

Danger

#### Hazard statements

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

#### Precautionary statements

P102 Keep out of reach of children.  
P101 If medical advice is needed, have product container or label at hand.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing vapour/ spray.  
P271 Use only outdoors or in a well-ventilated area.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 If eye irritation persists: Get medical advice/ attention.  
P501 Dispose of contents/ container in accordance with national regulations.

#### Contains

PROPAN-2-OL

#### Supplementary precautionary statements

P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P264 Wash contaminated skin thoroughly after handling.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTRE/doctor if you feel unwell.  
P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### 2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>PROPAN-2-OL</b>		<b>30-60%</b>
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25-xxxx
<b>Classification</b>		
Flam. Liq. 2 - H225		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		

**317/V604 - PATENT KNOTTING**

<b>ETHANOL</b>		<b>10-30%</b>
CAS number: 64-17-5	EC number: 200-578-6	REACH registration number: 01-2119457610-43-xxxx
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11	
<b>METHANOL</b>		<b>&lt;1%</b>
CAS number: 67-56-1	EC number: 200-659-6	
<b>Classification</b> Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 T;R23/24/25,R39/23/24/25	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures**

<b>General information</b>	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
<b>Skin contact</b>	Rinse with water.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

**4.2. Most important symptoms and effects, both acute and delayed**

<b>General information</b>	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	A single exposure may cause the following adverse effects: Coughing, chest tightness, feeling of chest pressure. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic.

## 317/V604 - PATENT KNOTTING

<b>Ingestion</b>	A single exposure may cause the following adverse effects: Confusion, agitation and/or excitation. Symptoms following overexposure may include the following: May cause nausea, headache, dizziness and intoxication. Unconsciousness.
<b>Skin contact</b>	A single exposure may cause the following adverse effects: Temporary irritation. Prolonged contact may cause dryness of the skin. Discoloration of the skin.
<b>Eye contact</b>	A single exposure may cause the following adverse effects: Redness. Irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

**Suitable extinguishing media** Flammable liquid and vapour. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up.

**Hazardous combustion products** Hydrocarbons. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Alcohols.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Provide adequate ventilation.

### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

## 317/V604 - PATENT KNOTTING

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment.

**Advice on general occupational hygiene** Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store away from incompatible materials (see Section 10). Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

**Storage class** Unspecified storage.

#### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

**Usage description** Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m<sup>3</sup>

##### ETHANOL

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m<sup>3</sup>

##### METHANOL

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 266 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 250 ppm(Sk) 333 mg/m<sup>3</sup>(Sk)

WEL = Workplace Exposure Limit.

#### PROPAN-2-OL (CAS: 67-63-0)

**317/V604 - PATENT KNOTTING**

<b>DNEL</b>	<p>Consumer - Inhalation; Long term systemic effects: 89 mg/m<sup>3</sup></p> <p>Consumer - Dermal; Long term systemic effects: 319 mg/kg/day</p> <p>Industry - Inhalation; Long term systemic effects: 500 mg/m<sup>3</sup></p> <p>Industry - Dermal; Long term systemic effects: 888 mg/kg/day</p> <p>Consumer - Oral; Long term systemic effects: 26 mg/kg/day</p>
<b>PNEC</b>	<ul style="list-style-type: none"> <li>- Soil; 28 mg/kg</li> <li>- Sediment; 552 mg/kg</li> <li>- Fresh water; 140.9 mg/l</li> <li>- STP; 2251 mg/l</li> <li>- marine water; 140.9 mg/l</li> <li>- ; Intermittent release 140.9 mg/l</li> </ul>

**ETHANOL (CAS: 64-17-5)**

<b>DNEL</b>	<p>Workers - Inhalation; Long term systemic effects: 950 mg/m<sup>3</sup></p> <p>Workers - Inhalation; Short term local effects: 1900 mg/m<sup>3</sup></p> <p>Workers - Dermal; Long term systemic effects: 343 mg/kg/day</p> <p>Consumer - Inhalation; Long term systemic effects: 114 mg/m<sup>3</sup></p> <p>Consumer - Inhalation; Short term local effects: 950 mg/m<sup>3</sup></p> <p>Consumer - Dermal; Long term systemic effects: 206 mg/kg/day</p> <p>Consumer - Oral; Long term systemic effects: 87 mg/kg/day</p>
<b>PNEC</b>	<ul style="list-style-type: none"> <li>- Fresh water; 0.96 mg/l</li> <li>- marine water; 0.79 mg/l</li> <li>- Intermittent release; 2.75 mg/l</li> <li>- STP; 580 mg/l</li> <li>- Sediment (Freshwater); 3.6 mg/kg/day</li> <li>- Sediment (Marinewater); 2.9 mg/kg/day</li> <li>- Soil; 0.63 mg/kg/day</li> </ul>

**METHANOL (CAS: 67-56-1)**

<b>DNEL</b>	<p>Workers - Dermal; Short term systemic effects: 40 mg/kg/day</p> <p>Workers - Inhalation; Short term systemic effects: 260 mg/m<sup>3</sup></p> <p>Workers - Inhalation; Short term systemic effects: 40 mg/m<sup>3</sup></p> <p>Workers - Dermal; Long term systemic effects: 40 mg/kg/day</p> <p>Workers - Inhalation; Long term systemic effects: 260 mg/m<sup>3</sup></p> <p>Workers - Inhalation; Long term local effects: 260 mg/m<sup>3</sup></p> <p>Consumer - Dermal; Short term systemic effects: 8 mg/kg/day</p> <p>Consumer - Inhalation; Short term systemic effects: 50 mg/m<sup>3</sup></p> <p>Consumer - Oral; Short term systemic effects: 8 mg/kg/day</p> <p>Consumer - Inhalation; Long term local effects: 50 mg/m<sup>3</sup></p> <p>Consumer - Oral; Long term systemic effects: 8 mg/kg/day</p> <p>Consumer - Inhalation; Long term systemic effects: 50 mg/m<sup>3</sup></p> <p>Consumer - Dermal; Long term systemic effects: 8 mg/kg/day</p> <p>Consumer - Inhalation; Short term local effects: 50 mg/m<sup>3</sup></p>
<b>PNEC</b>	<ul style="list-style-type: none"> <li>- Fresh water; 154 mg/l</li> <li>- marine water; 15.4 mg/l</li> <li>- Sediment; 570.4 mg/kg</li> <li>- Soil; 23.5 mg/kg</li> <li>- STP; 100 mg/l</li> <li>- Intermittent release; 1540 mg/l</li> </ul>

**8.2. Exposure controls**

## 317/V604 - PATENT KNOTTING

### Protective equipment



### Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

### Personal protection

Unprotected persons should be kept away from treated areas.

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. For exposure up to 4 hours, wear gloves made of the following material: Nitrile rubber. The selected gloves should have a breakthrough time of at least 4 hours.

### Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

### Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

### Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140. It is recommended to use respiratory equipment with combination filter, type A2/P2.

### Environmental exposure controls

Keep container tightly sealed when not in use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Dark coloured liquid. Slightly viscous liquid.
Colour	Brown.

## 317/V604 - PATENT KNOTTING

<b>Odour</b>	Strong. Alcoholic.
<b>Flash point</b>	12 approx. °C Closed cup.
<b>Vapour density</b>	heavier than air
<b>Relative density</b>	0.93 @ @ 20 C°C
<b>Solubility(ies)</b>	Slightly soluble in water.
<b>Auto-ignition temperature</b>	400 approx. °C
<b>Viscosity</b>	<30 seconds 3mm ISO cup method ISO 2431 s @ °C

### 9.2. Other information

<b>Volatility</b>	27
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 581 g/litre.

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

<b>Reactivity</b>	See the other subsections of this section for further details.
-------------------	--

### 10.2. Chemical stability

<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
------------------	---

### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	No potentially hazardous reactions known.
---	---

### 10.4. Conditions to avoid

<b>Conditions to avoid</b>	Avoid heat. Containers can burst violently or explode when heated, due to excessive pressure build-up.
----------------------------	--

### 10.5. Incompatible materials

<b>Materials to avoid</b>	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
---------------------------	--

### 10.6. Hazardous decomposition products

<b>Hazardous decomposition products</b>	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.
---	--

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

<b>ATE oral (mg/kg)</b>	14,484.36
-------------------------	-----------

#### Acute toxicity - dermal

<b>ATE dermal (mg/kg)</b>	43,453.07
---------------------------	-----------

#### Acute toxicity - inhalation

<b>ATE inhalation (vapours mg/l)</b>	434.53
--------------------------------------	--------

### Toxicological information on ingredients.

## PROPAN-2-OL



**317/V604 - PATENT KNOTTING****Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,840.0

**Species** Rat

**ATE oral (mg/kg)** 5,840.0

**Skin corrosion/irritation**

**Extreme pH** Not irritating.

**Skin sensitisation**

**Skin sensitisation** Not sensitising.

**Carcinogenicity**

**Carcinogenicity** No evidence of carcinogenicity in animal studies

**Reproductive toxicity**

**Reproductive toxicity - fertility** No evidence of reproductive toxicity in animal studies

**Ingestion**

Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

**Eye contact**

Severe irritation, burning and tearing.

**METHANOL****Acute toxicity - oral**

**ATE oral (mg/kg)** 100.0

**Acute toxicity - inhalation**

**ATE inhalation (vapours mg/l)** 3.0

**SECTION 12: Ecological information****12.1. Toxicity****Ecological information on ingredients.****PROPAN-2-OL****Acute aquatic toxicity**

**Acute toxicity - fish** LC50, 96 hours: 9640 mg/l, Pimephales promelas (Fat-head Minnow)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 9714 (24 hrs) mg/l, Daphnia magna

**Acute toxicity - aquatic plants** , > 72 hours: 100 mg/l, Scenedesmus subspicatus

**Acute toxicity - microorganisms** EC<sub>50</sub>, >: 100 mg/l,

**METHANOL****Acute aquatic toxicity**

## 317/V604 - PATENT KNOTTING

<b>Acute toxicity - fish</b>	LC <sub>50</sub> , 96 hours: 15400 mg/l, Lepomis macrochirus (Bluegill)
<b>Acute toxicity - aquatic invertebrates</b>	EC <sub>50</sub> , 24 hours: 20803 mg/l, Daphnia magna
<b>Acute toxicity - aquatic plants</b>	EC <sub>50</sub> , 96 hours: 22000 mg/l, Pseudokirchneriella subcapitata
<b>Acute toxicity - microorganisms</b>	IC <sub>50</sub> , 3 hours: > 1000 mg/l, Activated sludge
<b><u>Chronic aquatic toxicity</u></b>	
<b>Chronic toxicity - fish early life stage</b>	LOEC, 200 hours: 7900 mg/l, Fish NOEC, 28 days: 446.7 mg/l, Fish

### 12.2. Persistence and degradability

#### Ecological information on ingredients.

##### PROPAN-2-OL

<b>Biodegradation</b>	- 53 Degradation (%): 5 days The substance is readily biodegradable.
-----------------------	---

### 12.3. Bioaccumulative potential

#### Ecological information on ingredients.

##### PROPAN-2-OL

<b>Bioaccumulative potential</b>	The product is not bioaccumulating.
----------------------------------	-------------------------------------

##### METHANOL

<b>Bioaccumulative potential</b>	BCF: < 10,
<b>Partition coefficient</b>	log Kow: 0.77

### 12.4. Mobility in soil

#### Ecological information on ingredients.

##### PROPAN-2-OL

<b>Mobility</b>	The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.
-----------------	---

### 12.5. Results of PBT and vPvB assessment

#### Ecological information on ingredients.

##### PROPAN-2-OL

<b>Results of PBT and vPvB assessment</b>	This substance is not classified as PBT or vPvB according to current EU criteria.
---	---

##### METHANOL

<b>Results of PBT and vPvB assessment</b>	This substance is not classified as PBT or vPvB according to current EU criteria.
---	---

### 12.6. Other adverse effects

#### **SECTION 13: Disposal considerations**

## 317/V604 - PATENT KNOTTING

### 13.1. Waste treatment methods

**Disposal methods** Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Incineration or landfill should only be considered when recycling is not feasible.

**Waste class** When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11\* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11\* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

### SECTION 14: Transport information

**General** For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

#### 14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT

Proper shipping name (ICAO) PAINT

#### 14.3. Transport hazard class(es)

ADR/RID class 3

IMDG class 3

ICAO class/division 3

#### Transport labels



#### 14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ICAO packing group II

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

#### 14.6. Special precautions for user

## 317/V604 - PATENT KNOTTING

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**EmS** F-E, S-E

**Tunnel restriction code** (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to** Not applicable.

**Annex II of MARPOL 73/78 and the IBC Code**

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	Health and Safety at Work etc. Act 1974 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits.
<b>EU legislation</b>	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
<b>Guidance</b>	Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### Inventories

#### **EU - EINECS/ELINCS**

None of the ingredients are listed or exempt.

## SECTION 16: Other information

<b>Abbreviations and acronyms used in the safety data sheet</b>	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. IATA: International Air Transport Association. ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air. IMDG: International Maritime Dangerous Goods. CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate. LC <sub>50</sub> : Lethal Concentration to 50 % of a test population. LD <sub>50</sub> : Lethal Dose to 50% of a test population (Median Lethal Dose). EC <sub>50</sub> : 50% of maximal Effective Concentration. PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.
<b>Training advice</b>	Read and follow manufacturer's recommendations.

## 317/V604 - PATENT KNOTTING

<b>Revision comments</b>	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Unique Formula Identifier (UFI) added Addition of EU supplier information
<b>Issued by</b>	Technical Dept. (P.E.)
<b>Revision date</b>	18/02/2021
<b>Revision</b>	5.3
<b>Supersedes date</b>	27/01/2021
<b>SDS number</b>	10759
<b>SDS status</b>	Approved.
<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapour. H301 Toxic if swallowed. H311 Toxic in contact with skin. H319 Causes serious eye irritation. H331 Toxic if inhaled. H336 May cause drowsiness or dizziness. H370 Causes damage to organs (Central nervous system, Eyes) if swallowed or if inhaled.
<b>Signature</b>	Initials_____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.