



**Lacq Paquet Varnish** is an extremely strong no-nonsense urethane acrylate-based varnish for hardwood and parquet floors with extremely high wear resistance and can also be used on wood furniture.

Parquet lacquer is easy to apply and is recommended for wood floors that are used intensively.

#### **SPECIFIC PROPERTIES:**

- High wear resistance
- Flexible
- Available in Matt and Satin Gloss
- Does not yellow
- 32% volume solids content
- Easy to maintain
- Water-based
- Low odour
- Suitable for all types of wood
- Floors, furniture
- No build-up or overlapping
- Recoatable (at 20°C and 40-65% RH) after 1.5 - 2 hours
- Fully dry in 24 hours
- Fully hardened after 7 days (cleanable)

#### **INSTRUCTIONS FOR USE:**

##### **Untreated timber.**

1. Thoroughly degrease floor with Fluxaf Proclean; degrease tropical wood varieties such as Teak, Wengé with a thinner.
2. Sand the surface in the direction of the grain. Use a P120 - P150 grit for this purpose. After sanding, thoroughly vacuum remove any remaining dust.
3. Thoroughly stir the product.
4. The product can be applied with a roller, brush or spray.
5. For maximum protection we recommend the application of 3 coats. It is recoatable after 1.5-2 hours.
6. Lightly sand in between coats with a P220 or P320 grit.
7. Always provide for proper ventilation.

**Treated wood.** (other than with Lacq Parketlak)

1. First, thoroughly remove all old lacquer, wax or oil layers, because these can have a negative effect on the adhesion and quality of the Lacq Parketlak. This can be accomplished with the appropriate sanders and/or cleaning agents.
2. Sand the surface in the direction of the grain. Use a P120 - P150 grit for this purpose. After sanding, thoroughly vacuum and remove all remaining dust.
3. Thoroughly stir the product.
4. The product can be applied with a roller, brush or spray.
5. For maximum protection we recommend the application of 3 coats. It is recoatable after 1.5-2 hours.
6. Lightly sand in between coats with a P220 or P240 grit.
7. Always ensure proper ventilation.

All tools used can be cleaned with **water**.

**COVERAGE:**

12-15 m<sup>2</sup>/L, depending on type of wood, sanding method and method of application.

*This coverage is indicative. Results are highly dependent on the type of wood, application and preparation. We recommend you set up a trial area to determine the exact coverage and result.*

**Available in:**

750 ml and 2.5 l.

**STORAGE**

Lacq Parketlak can be stored for 12 months at between 5 and 35 degrees C° in its original unopened packaging.

**NOTE:**

**The product is ready for use and therefore should not be thinned!**

The action of this product relies on many years of practical experience and research. We guarantee that the quality of the work performed in accordance with our systems complies with the properties identified by Vliegenthart BV, provided that the instructions issued by us are strictly adhered to and the work is carried out in accordance with the highest standards. We expressly disclaim any liability when the end result is unfavourably affected by factors over which we do not have any control. The buyer, using the means normally expected to be at his or her disposal, must check whether the supplied products are suitable for the planned application.

This technical data sheet is no longer valid after the publication of a new version.